

SILVYN® KLICK 90° N/KLICK 90° P/KLICK 90° M

Angled connectors for SILVYN® RILL PA 6 & PA 12 conduit



SILVYN® KLICK-90° is available with NPT, PG & metric threads. Use this 90° angled conduit gland to create a quick, secure connection with SILVYN® RILL conduit.

Approvals



Complete the installation



SILVYN®
RILL PA 6
page 563



SILVYN®
RILL PA 12
page 565

Technical data

Material:	silicone-free polyamide	Color:	black or gray
Temperature range:	-40°C to +115°C	IP Protection:	IP67 IP69 acc. to DIN 40050 T.9

Part number		Thread	Conduit outer diameter		Thread length		Pack size	SILVYN® RILL PA 6		SILVYN® RILL PA 12	
black	gray		in	mm	in	mm		black	gray	black	gray
NPT thread											
61800015	—	NPT ¼"	0.394	10.0	0.394	10.0	50	61746935	61746939	61815105	61815100
61800025	—	NPT ¼"	0.512	13.0	0.414	10.5	50	61746945	61746940	61815115	61815110
61800035*	—	NPT ⅜"	0.622	15.8	0.472	12.0	50	61746955	61746950	61815125	61815120
61800045	—	NPT ½"	0.835	21.2	0.512	13.0	50	61746965	61746960	61815135	61815130
61800055*	—	NPT ¾"	1.122	28.5	0.551	14.0	25	61746975	61746970	61815145	61815140
61800065*	—	NPT 1"	1.358	34.5	0.630	16.0	10	61746985	61746980	61815155	61815150
61800075	—	NPT 1¼"	1.673	42.5	0.709	18.0	10	61746995	61746990	61815165	61815160
61800084	—	NPT 1½"	2.146	54.5	0.709	18.0	10	61747005	61747000	61815175	61815170
PG thread											
61801025	61801020	PG 9	0.512	13.0	0.394	10.0	50	61746945	61746940	61815115	61815110
61801035	61801030	PG 11	0.622	15.8	0.394	10.0	50	61746955	61746950	61815125	61815120
56000105	56000100	PG 13	0.728	18.5	0.433	11.0	50	61747015	61747010	61815185	61815180
61801045	61801040	PG 16	0.835	21.2	0.472	12.0	50	61746965	61746960	61815135	61815130
61801055	61801050	PG 21	1.122	28.5	0.472	12.0	25	61746975	61746970	61815145	61815140
61801065	61801060	PG 29	1.358	34.5	0.472	12.0	10	61746985	61746980	61815155	61815150
61801075	61801061	PG 36	1.673	42.5	0.551	14.0	10	61746995	61746990	61747085	61714200
61801085	61801062	PG 48	2.146	54.5	0.551	14.0	5	61747005	61747000	61747095	61714210
Metric thread											
55501115	55501110	M10 x 1.0	0.394	10.0	0.472	12.0	50	61746935	61746939	61815105	61815100
55501125	55501120	M12 x 1.5	0.512	13.0	0.472	12.0	50	61746945	61746940	61815115	61815110
55501145	55501140	M16 x 1.5	0.622	15.8	0.472	12.0	50	61746955	61746950	61815125	61815120
55501165	55501160	M20 x 1.5	0.835	21.2	0.512	13.0	50	61746965	61746960	61815135	61815130
55501185	55501180	M25 x 1.5	1.122	28.5	0.512	13.0	25	61746975	61746970	61815145	61815140
55501205	55501200	M32 x 1.5	1.358	34.5	0.591	15.0	10	61746985	61746980	61815155	61815150
55501225	55501220	M40 x 1.5	1.673	42.5	0.591	15.0	10	61746995	61746990	61815165	61815160
55501245	55501240	M50 x 1.5	2.146	54.5	0.630	16.0	5	61747005	61747000	61815175	61815170
55501255	55501250	M63 x 1.5	2.146	54.5	0.630	16.0	5	61747005	61747000	61815175	61815170

* CSA approved