



SKINTOP® CLICK/CLICK-R


Strain relief with quick "click" insertion system




Complete the installation



SKINTOP®
DIX bushing
page 545



Plugs
page 522



Removal tool

SKINTOP® CLICK is an innovative cable insertion system that provides fast, highly flexible assembly. Easy snap-in-place installation results in fixed, centered, strain relief with maximum protection in seconds. Mounting hole is based on metric thread. SKINTOP® CLICK-R includes reducer bushing.

Recommended applications

Applications where locknut installation is difficult to reach or to secure, such as dual wall enclosures and temperature controlled assemblies where insulation is used

Approvals



Application advantage

- Up to 70% installation time savings due to innovative CLICK system
- Ideal for hard-to-reach dual wall enclosures and limited access spaces
- Reduced inventory as no locknuts are required
- The heavy duty SKINTOP® design provides great pullout strength and very reliable strain relief
- Superior integrated locking mechanism includes an internal ratchet for vibration-proof protection

Accessories



1 removal tool included per pack. Additional tools are available; see table for part numbers.

Technical data

Material:

- body: special polyamide
- seal: special elastomer

Temperature range:

- static: -40°C to +100°C
- dynamic: -20°C to +100°C

Color:

black (RAL 9005), UV resistant
gray (RAL 7001)

IP Protection:

- M12: IP68, 4 bar
- M16 - M25: IP68, 5 bar
- M32: IP68, 1 bar

Part number*	Mounting hole size	UL status	Clamping range (øF)		Wrenching flats (SW1/SW2)	Overall length (C)	Thread length (D)	Hole (øM)	Pack size	Removal tool	
			in	mm							
Standard											
53112923	53112921	M12	Recognized	0.177-0.276	4.5-7	0.591/0.709	1.576	0.315	0.484 (-.008)	50	53112696
53112882	53112876	M16	Recognized	0.197-0.394	5-9	0.748/0.866	1.654	0.315	0.642 (-.008)	50	53112697
53112883	53112877	M20	Listed	0.276-0.512	7-13	0.985/1.063	1.792	0.315	0.799 (-.008)	25	53112698
53112884	53112878	M25	Listed	0.354-0.669	9-17	1.182/1.339	1.910	0.315	0.996 (-.008)	25	53112699
53112924	53112922	M32	Listed	0.433-0.787	11-20	1.417/1.576	2.167	0.315	1.272 (-.008)	25	53112797
Reducer bushing											
53112929	53112927	M12	Recognized	0.1385-0.197	3.5-5	0.591/0.709	1.576	0.315	0.484 (-.008)	50	53112696
53112885	53112879	M16	Recognized	0.157-0.276	4-7	0.748/0.866	1.654	0.315	0.642 (-.008)	50	53112697
53112886	53112880	M20	Listed	0.197-0.394	5-10	0.985/1.063	1.792	0.315	0.799 (-.008)	25	53112698
53112887	53112881	M25	Listed	0.236-0.512	6-13	1.182/1.339	1.910	0.315	0.996 (-.008)	25	53112699
53112931	53112928	M32	Listed	0.276-0.591	7-15	1.417/1.576	2.167	0.315	1.272 (-.008)	25	53112797

* Suitable for wall thickness of 1 - 4 mm (0.039 - 0.157 in)

If not otherwise specified, all values relating to the product are nominal values. Photographs are not to scale and are not true representations of the products in question.