

# ETHERLINE® 4 pair: CAT.5e; stationary

## Industrial Ethernet cable for stationary applications

LAPP KABEL STUTTGART ETHERLINE® CAT.5e



ETHERLINE® 4 pair cables for stationary applications are suitable for CAT.5e data transmission. Designed with a foil and braid shield, the cable is protected against EMI and can be used in areas where reliable data transmission is key. The cable is available with a PUR or halogen-free jacket, or with a double halogen-free inner and outer jacket.

### Construction

- Conductors:** solid bare copper
- Pairs:** 4 pairs twisted together
- Insulation:** foam skin
- Shielding:** foil and tinned copper braid
- Jacket:** polyurethane or halogen-free; teal • 2170298: halogen-free inner & outer jackets

### Recommended applications

Stationary applications; industrial field and cell level networking; PLCs, sensors, and other network devices; dry and damp rooms

### Application advantage

- Suitable for EtherCAT® & EtherNet/IP applications
- Excellent EMI protection
- Flame retardant
- Suitable for PoE per IEEE 802.3at

### Approvals



#### Cable attributes page 648

See attribute list by part number on page 234

#### Complete the installation



SKINTOP® MS-SC  
page 522



RJ45 connectors  
page 257

#### ÖLFLEX® CONNECT solution



ÖLFLEX® CONNECT CABLES  
page 605

### Technical data

<p> <b>Minimum bend radius:</b> - for stationary use: 8 x cable diameter</p> <p> <b>Temperature range:</b> -30°C to +80°C</p> <p> <b>Nominal voltage:</b> (not for power applications) - 2170297: 1000V - 2170296, 2170298: 125V</p> <p> <b>Test voltage:</b> 1000V</p>	<p> <b>Characteristic impedance:</b> 100Ω ± 15Ω</p> <p> <b>Color code:</b> white/blue &amp; blue, white/orange &amp; orange, white/green &amp; green, white/brown &amp; brown</p> <p> <b>Approvals:</b> UL: AWM 21576 (2170297) Canada: cRU AWM I/II A/B FT2 (2170297) Additional: RoHS</p>
---	---

Part number	Construction	Stranding	Jacket material	Jacket color	Approvals	Fast connect	PoE	Nominal outer diameter		Approx. weight lbs/mft	SKINTOP® MS-SC PG thread
								in	mm		
<b>CAT.5e</b>											
2170296	24 AWG/4pr	solid	halogen-free	teal	–	no	yes	0.248	6.3	36	53112210
2170297	24 AWG/4pr	solid	PUR	teal	UL/CSA AWM, 1000V	no	yes	0.248	6.3	42	53112210
2170298	24 AWG/4pr	solid	halogen-free*	teal	–	no	yes	0.296	7.5	54	53112220

\* Inner and outer jacket