


SKINTOP® MS-M-XL/MSR-M-XL

Nickel-plated brass strain relief with extended metric thread



Complete the installation

SKINTOP®
DIX bushing
page 545Plugs
page 548SKINDICHT®
SM locknuts
page 542

SKINTOP® MS-M-XL/MSR-M-XL is a superior quality, liquid-tight, metallic cable gland intended for applications where ruggedness, durability, and long threads are required. SKINTOP® MSR-M-XL includes reducer bushing.

Approvals



Application advantage

- Ideal for heavy wall applications or for use with locknuts where tapped holes cannot be provided
- Suitable for use in areas with high demands on special mechanical and chemical stability
- The heavy duty SKINTOP® design provides great pull-out strength and very reliable strain relief
- Extended temperature range due to the nickel-plated brass body
- Generous high-quality neoprene bushing and NBR O-ring provide a liquid-tight and dust-proof hermetic seal

Technical data



Material:

- body: nickel-plated brass
- insert: polyamide
- bushing: CR
- O-ring: NBR



Temperature range:

- static: -40°C to +100°C
- dynamic: -25°C to +100°C



Locknuts:

add SKINDICHT® SM-M, page 542



IP Protection:

- seal: 70 PSI
IP68, 10 bar
IP69
NEMA 1, 4X, 6, 12

Part number	Thread	Clamping range (øF)		Wrenching flats (SW) in	Overall length (C) in	Thread length (D) in	Pack size
		in	mm				
Standard							
53112005	M12 x 1.5	0.138 - 0.276	3.5 - 7	0.630	1.292	0.472	100
53112015	M16 x 1.5	0.177 - 0.394	4.5 - 10	0.788	1.457	0.472	50
53112025	M20 x 1.5	0.276 - 0.512	7 - 13	0.945	1.556	0.472	50
53112035	M25 x 1.5	0.354 - 0.669	9 - 17	1.142	1.635	0.472	25
53112045	M32 x 1.5	0.433 - 0.827	11 - 21	1.418	1.899	0.591	25
53112055	M40 x 1.5	0.748 - 1.103	19 - 28	1.773	2.107	0.591	10
53112065	M50 x 1.5	1.063 - 1.379	27 - 35	2.127	2.245	0.591	5
Reducer bushing							
53112105	M12 x 1.5	0.078 - 0.197	2 - 5	0.630	1.292	0.472	100
53112115	M16 x 1.5	0.078 - 0.276	2 - 7	0.788	1.457	0.472	50
53112125	M20 x 1.5	0.197 - 0.394	5 - 10	0.945	1.556	0.472	50
53112135	M25 x 1.5	0.236 - 0.512	6 - 13	1.142	1.635	0.472	25
53112145	M32 x 1.5	0.276 - 0.591	7 - 15	1.418	1.899	0.591	25
53112155	M40 x 1.5	0.591 - 0.906	15 - 23	1.773	2.107	0.591	10
53112165	M50 x 1.5	0.866 - 1.142	22 - 29	2.127	2.245	0.591	5

If not otherwise specified, all values relating to the product are nominal values.
Photographs are not to scale and are not true representations of the products in question.