

## Datasheet

### RS Pro Hours Run Meter, 6 digits, Digital, Spade Terminal Connection, 10 → 80 V dc

RS Stock No: **896-6939**



## Product Details

RS Pro hours run meter has a robust design that enables a high degree of accuracy and it has 50.8 mm cut-out size. The design of this round meter makes it totally sealed from dust and moisture. It has 6 digit display with digital spade terminal connection and has a supply voltage of 10 to 80 V dc.

## Features and Benefits

- 7 different bezel style models
- Panel mount
- 6 digits non-resettable with automatic recycle to zero
- Compact and robust design provides shock and vibration protection
- Wide supply voltage range
- IP66 protection

## Specifications:

Approvals	CE; cRUus; NEMA 4X; RoHS Compliant; SAE
Count Direction	Up
Function	Hour Meter
Meter Type	Electronic
Shape	Round
Cutout Height	24.1 mm
Depth	70.5 mm
Maximum Count Frequency	50/60 Hz
Maximum Measurement	99999.9 h
Measurement Range	0 to 99999.9 h
Meter Accuracy	±0.02%
Minimum Measurement	0 h
Minimum Operating Temperature	-40°C
Number of Digits	6
Weight	47 g
Connection Type	Spade
Count Capacity	99999.9 h
Cutout Size	50.8 (dia.) mm
Digit Height	3.6 mm
Display Type	Digital
Input Type	Voltage
Mounting Type	Panel Mount
Reset Method	No Reset
Supply Voltage	10 to 80 V dc
Humidity Rating	95%
IP Rating	IP65
Power Rating	0.25 VA



## Hours Run Meters

### Bezel styles:

### RS Stock No's







**A** Rectangular Bezel: 896-6905, 896-6914,

**B** Rectangular 2 hole bezel: 896-6927, 896-6936, 896-6923


**C** Round Bezel: 896-6933, 896-6939, 896-6942

**D** Round 3 hole Bezel: 896-6917, 896-6911, 896-6920

**E** Square Bezel: 896-6894, 896-6898





### Panel cutout :



Max. Panel Thickness; 1.129 (0.76) to 0.401 (10.20)  
Panel Cut-out dimensions - Tolerance +/- 0.010 (0.30)  
All Dimensions are in inches, Values in ( ) = mm


### Connections:



**CAUTION :** 1) Screw to be tightened with flat head screwdriver with tip size 4.3 x 0.6 mm.

**MOUNTING FRAME 896-6908**

55x55mm Bezel for 896-6894 and 896-6898



**MOUNTING FRAME 896-6901**

72x72mm Bezel for 896-6894 and 896-6898

