



T CLASS FUSEHOLDER COVER  
 CAT. NO. CT6100/200M  
 600V 100/200A

NOTES:

1. AGENCY INFORMATION:  
 UL FILE NO. E181825  
 UL GUIDE CARD NO. JDVS
2. MATERIAL:  
 INSULTOR - THERMOPLASTIC CLEAR  
 TEMP. RATINGS 125 °C (257 °F)
3. RATINGS:  
 MAXIMUM AMP PER POLE - 200A.  
 BASED ON NEC WIRE RATINGS CODE: 75 °C

DRAWING REVISION B		REVISION BY R. SCHECKELHOFF	DATE 6/12/19	TOLERANCES UNLESS OTHERWISE SPECIFIED:		DRAWN BY R. SCHECKELHOFF		REGAL <sup>TM</sup> Regal Beloit America, Inc.	
ECO ECO-0168493		APPROVED BY	DATE	.X ±0.1	.mm [+2.5]	ANGLE	DATE 5/17/18	DESCRIPTION COVER	
ECO DESCRIPTION LABEL ORIENTATION CHANGE				.XX ±0.03	[+0.76]	±7 30"	APPROVED BY	CT6100/200M	
<small>COPYRIGHT REGAL BELOIT AMERICA, INC. ALL RIGHTS RESERVED.                  PROPRIETARY AND CONFIDENTIAL INFORMATION - THIS DOCUMENT IS THE PROPERTY OF                  REGAL BELOIT AMERICA, INC. ("OWNER") AND CONTAINS OWNER'S PROPRIETARY                  INFORMATION. ANY PERSON, CORPORATION OR OTHER FIRM RECEIVING IT IS DEEMED                  BY RECEIVING IT, TO AGREE THAT IT, AND/OR ANY PART OF IT, SHALL NOT BE DISCLOSED                  TO ANY PERSON, CORPORATION OR OTHER ENTITY, DUPLICATED, AND/OR USED, EXCEPT                  AS EXPRESSLY APPROVED IN WRITING IN ADVANCE BY OWNER. THIS DOCUMENT SHALL                  BE RETURNED TO OWNER UPON REQUEST. IT MAY BE SUBJECT TO CERTAIN                  RESTRICTIONS UNDER APPLICABLE EXPORT CONTROL LAWS AND REGULATIONS.</small>				.XXX ±0.015	[±0.381]	REMOVE BURRS & BREAK SHARP EDGES: .003/.015 [±0.0127] X 45° CORNER FILLETS: R.02 [5.1]	DATE	MATERIAL	
				.XXXX ±0.0005	[±0.0127]	MACHINED SURFACES: 200/ 5.1	REFERENCE	PROCESS/FINISH	
				mm SHOWN IN [BRACKETS]		INCH/mm	THIRD ANGLE PROJECTION	SIZE A	DRAWING NUMBER 4250001
									SHEET 1 OF 2