Rittal - The System.

Faster – better – everywhere.

Roof-mounted fan, roof vent – SK 3139.110

Date: Oct 20, 2019



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Roof-mounted fan, roof vent – SK 3139.110 : 20.10.2019 build on www.rittal.com/ca-en



Product description	
Description:	Roof-mounted fan with a high protection category and flexible installation from the inside or outside.
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 21 without filter mat IP 55 including filter mat
Protection category NEMA:	with standard filter: NEMA 12
Supply includes:	Complete unit ready for connection, including filter mat
Note:	To improve energy efficiency and increase equipment service life, we recommend thermostats or temperature displays.
Product features	
Air throughput (unimpeded air flow):	500 m³/h (294.3 cfm)
Unimpeded air flow (without filter mats):	/ 525 m³/h
Unimpeded air flow (with filter mats):	/ 446 m³/h
Rated operating voltage:	115 V, 1~, 60 Hz
Dimensions:	Height: 133 mm (5.2 ") Width: 400 mm (16 ") Depth: 400 mm (16 ")

© Rittal 2019

Required mounting cut-out:	Width: 258 mm (10 ") Depth: 258 mm (10 ")
Installation depth:	34.6 mm
Temperature range:	Storage: -40 °C+70 °C Operation (environment): -20 °C+55 °C
Rated power Pel:	At 60 Hz: 65 W
Rated current max.:	At 60 Hz: 0.56 A
Miniature circuit- breaker/fuse:	3 A
Life span at 50 Hz:	69400 h
Life span at 60 Hz:	68000 h
Noise pressure level:	At 60 Hz: 54 dB(A)
Diagonal fan:	Radial, capacitor motor
Packaging unit:	1 pc(s).
Weight/packaging unit:	5.2 kg (11.4 lb.)
EAN:	4028177709164
Customs tariff number:	84145915
ETIM 6.0:	EC000320
ETIM 5.0:	EC000320
e CI@ss 8.0/8.1:	27180716
eCl@ss 7.0/7.1:	27180716
eCl@ss 6.0/6.1:	27180716
eCl@ss 5.1/5.1.4:	27180707
Product description:	SK roof-mounted fan TopTherm, 500/525 m³/h, 115 V, 1~, 50/60 Hz, WHD: 400 x 133 x 400 mm
A	

Approvals

© Rittal 2019

Approvals:	Approval overview CSA UL + C-UL - FTTA UR + C-UR
Certificates:	EAC
Declarations:	Declaration of conformity

© Rittal 2019 3