

Monitor - BL FPM 18.5 - 2402981

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



IP65-rated, 18.5-inch, flat-panel LCD monitor with projective capacitive touch screen

Product Description


The Baseline BL FPM 18.5 is an industrial flat-panel monitor that can be used in applications where a remote display location is required.

Your advantages

- ✓ 18.5-inch display
- ✓ DisplayPort 1.2, VGA, and DVI-I input ports
- ✓ Integrated configuration buttons
- ✓ Ambient operating temperatures from -10°C to 60°C
- ✓ 18.5-inch touch screen display



Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 202303
GTIN	4055626202303

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Display

Display	46.9 cm/18.5" TFT
Screen resolution	1366 x 768 Pixel(s) (WXGA)
Touch technology	projective-capacitive, ten-touch control
Brightness	300 cd/m ² , typical (adjustable)
Backlighting	LED
Display backlight MTBF	> 50000 h

Monitor - BL FPM 18.5 - 2402981

Technical data

Display

Colors	16.7 million colors
--------	---------------------

Monitor data

Network	Without network
Interfaces	1x USB Type A (For touch control only)
Monitor output	1x DisplayPort
	1x DVI-D
	1x VGA
Slots	without slots
Optical drive	without drive

General

Mounting type	VESA MIS-D, 100
	Front installation
Weight	6.24 kg

Ambient conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	-10 °C ... 60 °C
Ambient temperature (storage/transport)	-20 °C ... 75 °C
Permissible humidity (operation)	10 % ... 90 % (non-condensing)
Vibration (operation)	1g
Shock	15g, 11 ms impulse

Device supply

Supply voltage	24 V DC (±10 %)
Power supply unit	24 V DC

Standards and Regulations

Shock	15g, 11 ms impulse
Vibration (operation)	1g

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals

Approvals

Approvals





UL Listed / cUL Listed / EAC / cULus Listed

Monitor - BL FPM 18.5 - 2402981

Approvals

Ex Approvals

Approval details

UL Listed		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 238705
cUL Listed		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 238705
EAC			RU C- DE.A*08.B01708
cULus Listed			

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>