



ENGLISH

12V, 24W C14 Desktop SMPSU



Features:

- Universal input
- Small Compact Design
- 1 Year Warranty
- Efficiency Level VI
- UL,CUL,FCC,CE,RCM,GS Approved





ENGLISH

Specification	
RS Part Number	1753271
Rated Input Voltage	100-240V
Vibration Input Voltage Range	90-264V
Frequency Rated	50-60Hz
Frequency Vibration	47-63Hz
Input Current Rated	600mA Rms MAX
Inrush Current	No Damage
Leakage Current	No Damage
Average Efficiency	<3.5mA
Input Power(Output:No Load)	<0.1W (CEC & DOE LEVEL VI Compliant)
Output Voltage	12VDC
Output Max Current	2A
Output Min Current	0A
Line and Load Regulation	+/-5%
Over Voltage Protection	<16 V
Over Load Protection	< 3.5A output load
Short Circuit Protection	Output shut down auto recover
Ripple Voltage	150 mV (p-p) (100V-240V AC Input)
Hi-Pot	1500Vac or 2121VDC 10mA 1 min
Safety Approved	UL,IEC,CE,EN
Environment Standard	RoHS
AC Plug	IEC320/C14 Type
Size	(L)80.6 x (W)50 x (H)31 mm
Operating Temperature	0 to 40°C
Storage Temperature	-10 to 70°C
Operating Humidity	20% to 80%
Storage Humidity	10% to 90%
DC Connector	R/A 2.1 C+