





Modular TDX Panel Protector, 200 kA with Surge Counter – TDX200S120208



- Transient Discriminating (TD) Technology provides increased service life
- Modular design allows easy replacement of surge modules
- Built-in features include TD Technology, thermal protection and short circuit current fusing
- Compact NEMA®-4 enclosure design can be flush mounted or installed in a small space
- Status indication flag per mode, voltage presence LEDs, audible alarm and voltage-free contacts providing remote status monitoring
- 200kA 8/20 μ s maximum surge rating provides protection suitable for service entrance, main-distribution panels and highly exposed applications



Part Number	TDX200S120208
Nominal System Voltage (Un)	120/208 V
Distribution System	3Ph 4W+G
Max Continuous Operating Voltage (Uc)	170/276 VAC
Stand-off Voltage	240/415 VAC
Frequency	50 – 60 Hz
Short Circuit Current Rating (SCCR)	200 kA
Nominal Discharge Current (In), IEC	40 kA 8/20 μ s
Nominal Discharge Current (In), UL	20 kA 8/20 μ s
Max Discharge Current (Imax), Per Phase	200 kA 8/20 μ s
Impulse Current (Iimp), Per Mode	25 kA 10/350 μ s
Voltage Protection Rating (VPR), L-N	600 V @ 3 kA 1,200 V @ 20 kA
Protection Modes	L-N L-PE N-PE
Status Indication	LED Mechanical flag Audible alarm
Technology	TD technology with thermal disconnect Over-current replaceable cartridge fusing EMI/RFI filter
Remote Contacts	Yes
Lead Length	30"

Part Number	TDX200S120208
Lead Size	#10
Ground Lead Length	36"
Temperature	-40 to 176 °F
Enclosure Material	Metal
Enclosure Rating	IP 65 NEMA®-4
Mounting	3/4" straight nipple
Surge Counter	Yes
Depth (D)	3.07"
Height (H)	9.45"
Width (W)	5.12"
Unit Weight	4.4 lb
Certification Details	UL® 1449 Edition 4 Type 2, 20 kA Mode
Complies With	ANSI®/IEEE® C62.41.2-2002 Cat A, Cat B, Cat C ANSI®/IEEE® C62.41.2-2002 Scenario II, Exposure 3, 100 kA 8/20 µs, 10 kA 10/350 µs IEC® 61643-1 Class I, Class II
Replacement Module	TDS150M150
Certifications	CE C-Tick
Standard Packaging Quantity	1 pc
UPC	78285659392

ANSI is a registered trademark of American National Standards Institute. IEC is a registered trademark of the International Electrotechnical Commission. IEEE is a registered trademark of The Institute of Electrical and Electronics Engineers, Inc. NEMA is a registered service mark of National Electrical Manufacturers Association. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.