



Telephone Line Protector – SLP1RJ11A



- RJ11 sockets provide simple plug-in connection for 4 or 6 position RJ plugs
- Includes patch cord and adhesive mounting strips
- Provides both L-L and L-PE protection modes for comprehensive protection
- Automatic over-current protection



Part Number	SLP1RJ11A
Max Continuous Operating Voltage (Uc)	280 V
Max Discharge Current (Imax), Per Mode	20 kA 8/20 μ s
Voltage Protection Level (Up), T-R	110 V
Voltage Protection Level (Up), T/R-G	500 V @ 125 A
Rated Load Current (IL)	120 mA
Connection Type	RJ11
Ground Lead Length	6"
Lead Size	#18
Temperature	-40 to 149 °F
Depth (D)	1.1"
Height (H)	1 1/2"
Width (W)	3.06"
Unit Weight	0.11 lb
Certifications	A-Tick (Australia)
Standard Packaging Quantity	1 pc
UPC	78285652357
EAN-13	8711893060195

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.