

Datasheet

ENGLISH

Brass Pneumatic Quick Connect Coupling, Hose Barb, **4mm Hose Barb Connection**

RS Stock number 667-1857



021 [Quick Release Pneumatic Couplings]



Interchangeability

RECTUS 2 RECTUS 90,

CAMOZZI

Options

F-Straight Through flow

K - Chrome Plated

Temperature Range N - Nickel Plated

-20 C +100 C (-4 F +212 F) T - NPTF Thread

Order No

021 EG 10

021 EG 13

021 EG 17

V - Viton Seal

Working Pressure

0 - 35 bar (0 - 500 PSI)

Material

Flow Capacity

NW - 5

Coupler Body: Brass Nickel Plated Sleeve: Steel Body: Brass Nickel Plated

Length

36

38

38

Dia

16

16

16

Valve : Brass



Standard version

Balls: Stainless Steel

Buna (N)

Connection

g 1/8"

G 1/4"

G 3/8"

Springs: Stainless Steel

Locking O-Ring: Stainless Steel

14


17

19

Balls: Stainless Steel Seals: Buna (N)

Plug: Brass Nickel Plated


Couplers and Plugs



Male Thread Coup

7	
oler	

M 12X1,5	021 EG 12	17	39	16
M 14X1,5	021 EG 14	17	39	16
G 1/8"	021 DG 10	14	36	16
G 1/4"	021 DG 13	17	38	16
G 3/8"	021 DG 17	19	38	16
M 12X1,5	021 DG 12	17	38	16
M 14X1,5	021 DG 14	17	38	16



Female Thread Coupler



ENGLISH

	4mm 1/6"	021 HG 04	14	46	16
- 20 - 100	6mm 1/4"	021 HG 06	14	46	16
	8mm 5/16"	021 HG 08	14	46	16
	9mm 5/14"	021 HG 09	14	46	16
	10mm 3/8"	021 HG 10	14	46	16
Standart Hose Barb Coupler	6mm Parker 1/4"	021 HG 06 P	14	46	16
	4X6mm- M10X1	021 PG 04	14	41	16
Plastic Hose Coupler	6X8mm- M10X1	021 PG 06	14	41	16
	4X6mm- M10X1	021 SG 04	14	53	16
Plastic Hose Coupler With Spring	6X8mm- M12X1	021 SG 06	17	53	16
	4mm- M10X1	021 MG 04	14	60	16
Standart Hose Barb Plug	5mm- M12X1	021 MG 05	14	60	16
	6mm- M12X1	021 MG 06	17	60	16
	6mm- M12X1	021 MG 08	17	60	16
Plastic Hose Plug	4X6mm- M10X1	021 YG 04	14	125	16
	6X8mm- M10X1	021 YG 06	14	130	16



ENGLISH

	4mm 1/6"	021 HU 04		32	9
Male Thread Plug	5mm 1/5"	021 HU 05		32	9
	6mm 1/4"	021 HU 06		32	9
	8mm 5/16"	021 HU 08		32	9
	9mm 5/14	021 HU 09		33	12
Male Tillead Flug	10mm 3/8"	021 HU 10		33	12
	6mm Parker	021 HU 06 P		36	16
Female Thread Plug	4X6 mm- M10X1	021 PU 04		32	10
	6X8 mm- M12X1	021 PU 06		32	12
	4X6mm-	021 SU 04	14	44	
	M10X1				
Male Thread Plug	6X8mm- M12X1	021 SU 06	17	44	
	4 mm- M10X1	021 MU 04	14	50	
	5 mm-				
Male Thread Plug	M10X1	021 MU 05	14	50	
	6 mm-	021 MU 06	14	50	
	M12X1	021110 00	14	50	
	8 mm- M12X1	021 MU 08	14	50	
	9 mm- M12X1	021 MU 09	14	50	
	10 mm- M14X1	021 MU 10	17	50	



ENGLISH

	4X6mm-	021 YU 04		115
Male Thread Plug	M10X1 6X8 mm- M10X1	021 YU 06		120
	G1/8"	021 EU 10	14	25
	G1/4"	021 EU 13	17	28
	G3/8"	021 EU 17	19	28
	M 10X1	021 EU 10 M	14	26
Male Thread Plug	M 12X1,5	021 EU 12	17	28
	M 14X1,5	021 EU 14	17	28
	G 1/8"	021 DU 10	14	25
	G 1/4"	021 DU 13	17	26
	G 3/8"	021 DU 17	19	27
	M 10X1	021 DU 10 M	14	27
Male Thread Plug	M 12X1,5	021 DU 12	17	27
	M 14X1,5	021 DU 14	17	27