

## D-sub-data transmission cord for ASi Master in IP65, 1,5 m



ASi Master in IP65 (Specification 2.0)

Clamps	PIN	Function	Colour
1		PE	
2		SHIELD	
3	3	BUS P	green
4	8	BUS N	yellow
5	5	GRND	blue
6		PE	
7		SHIELD	
8		BUS P	
9		BUS N	
10	6	+5 V	red

Article no. BW1097	
Connection	RS 485 prefabricated cable
Storage temperature	-40°C ... +85°C
Operating temperature	-25°C ... +60°C
Protection category (IEC) EN 60529	connector IP65, plug IP20
Dimensions (L, W, H)	ca. 50 mm, 20 mm, 30 mm
Length	1,5 m

## D-sub-data transmission cord 9-pin, 1,8 m



Article no. BW1058	
Connection	D-Sub plug D-Sub socket
Length	1,8m
PIN 1 connected with PIN 1	

## D-sub-data transmission cord for ASi Gateways with CAN interface



ASi/CAN Gateway

Clamps	PIN	Function	Colour
1		n.c.	
2	7	CAN_H	white
3		SHIELD	
4	2	CAN_L	brown
5		n.c.	

Article no. BW1226	
Connection	D-subsocket, 5-pin COMBICON plug
Operating temperature	-40°C ... +85°C
Storage temperature	-25°C ... +60°C
Protection category (IEC) EN 60529	IP20
Dimensions (L, W, H)	ca. 50 mm, 20 mm, 30 mm
Length	1,5 m

## ASi addressing cable (with COMBICON connector) for direct addressing with ASi master



Article no. BW2324	
Connection	round connector 2-pin COMBICON-connector
Length	1,5 m
Connector (Master)	+ ASi -

## ASi addressing cable - infrared addressing adapter



Article no. BW1935	
Connection	infrared head/M12 connector
Length	1 m

## ASi addressing cable for addressing with handheld address programming device



Article no. BW3304	
Connection	ASi profile cable to M12
Length	1,0 m
scoop of delivery incl. 2 x substructure modules 60 mm x45 mm	

## ASi addressing cable for direct addressing with ASi master



Article no. BW3305	
Connection	ASi profile cable to COMBICON
Length	1,0 m
scoop of delivery incl. 2 x substructure modules 60 mm x45 mm	

## Connecting cable (Module/programming device)



Article no. BW1802	
Connection	round connector 2-pin/ M12 connector
Length	1,6 m

## Addressing plug



Article no. BW3340	
Color	black
Packing unit	5 pieces

## Protection cap for not used M12 sockets



Article no. BW2368	
Color	blue
Packing unit	50 pieces

## Protection cap for ASi-5 addressing socket, IP67, M12



Article no. BW4056	
Color	blue
Packing unit	50 pieces

## Memory plug cover



Article no. BW3155	
Color	blue
Packing unit	1 piece

## Cross-Link-cable for ASi/Ethernet Gateway



Article no. BW1304	
--------------------	--

## Serial cable for ASi Masters and ASi Monitors in stainless steel



Article no.	<b>BW1575</b>
Connection	D-Sub data cable 9-pin, Mini-Din plug 6-pin
Length	1,8 m

## USB connector cable for Safety Basic Monitor




<b>Article no.</b>	<b>BW2530</b>
Connection	USB type A – Micro USB
Length	1,8 m
Color	black

## ASi Probe



**Article no. BW1745**

## Chip card for Bihl+Wiedemann ASi products



**BW2079/BW2222**



**BW4055**

Article no.	BW2079	BW2222	BW4055
Memory capacity	32 kByte (256 kbit)	128 kByte (1024 kbit)	512 kByte (1024 kbit)
Weight	approx. 1 g		
Dimensions (L / W / H in mm)	25 / 15 / 1		
<b>Accessories:</b>			
<ul style="list-style-type: none"> <li>• <b>BW2079</b> for all ASi-3 Standard and all ASi-3 Safety products with chip card by Bihl + Wiedemann.</li> <li>• <b>BW2222</b> for ASi-3 Safety Monitors and ASi-3 Gateways in Stainless Steel Safety Version 4.X (for maximum 4 Safety configurations on a chip card).</li> <li>• <b>BW4055</b> for Gateways supporting ASi-5</li> </ul>			

## Memory Plug for Bihl+Wiedemann ASi products



<b>Article no.</b>	<b>BW3241</b>
Memory capacity	32 kByte (256 kbit)
Weight	approx. 2 g
Dimensions (L / W / H in mm)	26,5 / 7 / 4,5
Packing unit	10 pieces
<b>Accessorie for BW3064 ASi Safety Output Module (M12), IP67</b>	