

Product Number: 22078

Order Abbreviation: F20T12/CW

General Description: 20W, T12 preheat fluorescent lamp, Cool White phosphor, 4200K color temperature, 60 CRI. 9000 Avg rated life at 3 hrs/start



Product Information	
Abbrev. With Packaging Info.	F20T12CW 30/CS 1/SKU
Actual Length (in)	23.780
Actual Length (mm)	604.01
Average Rated Life (hr)	9000
Base	Medium Bipin
Bulb	T12
Color Rendering Index (CRI)	60
Color Temperature/CCT (K)	4200
Diameter (in)	1.591
Diameter (mm)	40.40
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	1200
Mean Lumens at 25C	1044
Nominal Length (in)	24.000
Nominal Length (mm)	609.60
Nominal Wattage (W)	20.00

Footnotes
<ul style="list-style-type: none">• Approximate initial lumens after 100 hours operation.• The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.• Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.• Preheat lamp, starter required.• Mean lumens are measured at 40% of average rated lamp life.• The distance between any parts of the lamp and any conductive surface of the luminaire should not be less than 3 mm (applies to all high frequency ballasted systems).• The lamp should not be in contact with any surface of the luminaire (applies to either high frequency or 60Hz ballasted systems).