

### Product type designation

**IWLAN panel feedthrough N-Connect/N-Connect Female/Female**  
 N-Connect Female/female Panel feedthrough, cabinet bushing, 2.4 GHz and 5 GHz for Wall thickness max. 4.5 mm



### Electrical data

Number of electrical connections	2
Type of electrical connection	N-Connect female/N-Connect female
Transmission frequency	0 ... 11 GHz
Impedance	50 Ω

### Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> <li>• during operation</li> <li>• during storage</li> <li>• during transport</li> </ul>	<p>-30 ... +100 °C</p> <p>-30 ... +100 °C</p> <p>-30 ... +100 °C</p>
Protection class IP	IP68

### Design, dimensions and weights

Diameter	20.7 mm
Length	38 mm
Net weight	55 g

### Standards, specifications, approvals

Certificate of suitability	
----------------------------	--

- RoHS conformity

Yes

## Further information / Internet-Links

### Internet-Link

- to website: TIA Selection Tool
- to website: Selector SIMATIC NET SELECTION TOOL
- to the website: IWLAN
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/tia-selection-tool>

<http://www.siemens.com/snst>

<http://www.siemens.com/iwlan>

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

**last modified:**

02/28/2020