

Control Power Transformer, 50va, PRI 380v, SEC 24v, Kit,



Figure similar

Product brand name	Control Power Transformer
Design of the product	Control power voltage
Special product feature	Complete kit
General technical data	
Weight [lb]	3.5 lb
Height x Width x Depth [in]	4 × 3 × 3.64 in
Ambient temperature [°F]	
• during operation	-4 ... +104 °F
Ambient temperature	
• during operation	-20 ... +40 °C
Country of origin	Mexico
Operating apparent output rated value	50 V·A
Enclosure	
Design of the housing	Open
Mounting/wiring	
Mounting position	Any
Mounting type	Surface mounting

Type of electrical connection at output for main current circuit	Screw-type terminals (touchsafe)
Type of electrical connection at input for main current circuit	Screw-type terminals (touchsafe)

Inputs/ Outputs	
Input dimensions of primary voltage	240/480vac
Output dimensions of secondary voltage	120vac
Phase number of the inputs	1
Electrical input frequency	50 ... 60 Hz
Input voltage _1	240 V
Input voltage _2	480 V
Phase number of the outputs	1
Electrical output frequency	60 ... 50 Hz
Output voltage _1 rated value	120 V
Certificate of suitability	UL / CSA

Further information	
Industrial Controls - Product Overview (Catalogs, Brochures,...) www.usa.siemens.com/iccatalog	
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/us/Catalog/product?mlfb=US2:KT8050P	
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/US/en/ps/US2:KT8050P	
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:KT8050P&lang=en	
Certificates/approvals https://support.industry.siemens.com/cs/US/en/ps/US2:KT8050P/certificate	

last modified: 03/03/2020