

FXD63B200 | US2:FXD63B200



SIEMENS LOW VOLTAGE SENTRON MOLDED CASE CIRCUIT BREAKER WITH THERMAL - MAGNETIC TRIP UNIT. STANDARD 40 DEG C BREAKER FD FRAME WITH STANDARD BREAKING CAPACITY AND NON INTERCHANGEABLE TRIP. MEETS UL 489 / IEC 60947-2 STANDARDS. 200A 3-POLE BREAKER (22KAIC AT 600V) (35KAIC AT 480V). SPECIAL FEATURES: NO LUGS INSTALLED. DIMENSIONS (W x H x D) IN: 4.5 x 9.5 x 4.

|                                                    |             |
|----------------------------------------------------|-------------|
| List Price                                         | Show prices |
| Customer Price                                     | Show prices |
| DataSheet in PDF                                   | Download    |
| Service & Support (Manuals, Certificates, FAQs...) | Download    |

Product

|                                       |                                                                                                                                                                                                                                                                                                                                                                         |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number (Market Facing Number) | FXD63B200   US2:FXD63B200                                                                                                                                                                                                                                                                                                                                               |
| Product Description                   | SIEMENS LOW VOLTAGE SENTRON MOLDED CASE CIRCUIT BREAKER WITH THERMAL - MAGNETIC TRIP UNIT. STANDARD 40 DEG C BREAKER FD FRAME WITH STANDARD BREAKING CAPACITY AND NON INTERCHANGEABLE TRIP. MEETS UL 489 / IEC 60947-2 STANDARDS. 200A 3-POLE BREAKER (22KAIC AT 600V) (35KAIC AT 480V). SPECIAL FEATURES: NO LUGS INSTALLED. DIMENSIONS (W x H x D) IN: 4.5 x 9.5 x 4. |
| Product family                        | Ordering Data Overview                                                                                                                                                                                                                                                                                                                                                  |
| Product Lifecycle (PLM)               | PM300:Active Product                                                                                                                                                                                                                                                                                                                                                    |

Delivery information

|                                |                       |
|--------------------------------|-----------------------|
| Export Control Regulations     | AL : N / ECCN : EAR99 |
| Standard lead time ex-works    | 20 Day/Days           |
| Net Weight (lb)                | 8.803 lb              |
| Product Dimensions (W x L x H) | Not available         |
| Packaging Dimension            | 5.354 x 6.89 x 11.024 |
| Package size unit of measure   | in                    |
| Quantity Unit                  | 1 Piece               |
| Packaging Quantity             | 1                     |

Additional Product Information

|                                                                          |                   |
|--------------------------------------------------------------------------|-------------------|
| EAN                                                                      | Not available     |
| UPC                                                                      | 783643211278      |
| Commodity Code                                                           | 8536200020        |
| LKZ_FDB/ CatalogID                                                       | LV10.1            |
| Product Group                                                            | 3741              |
| Country of origin                                                        | Mexico            |
| Compliance with the substance restrictions according to RoHS directive   | Since: 04/03/2009 |
| Returnable                                                               | Yes               |
| WEEE (2012/19/EU) Take-Back Obligation                                   | Yes               |
| REACH Art. 33 Duty to inform according to the current list of candidates |                   |

Classifications

|        | Version | Classification |
|--------|---------|----------------|
| eClass | 5.1     | 27-37-04-09    |
| eClass | 6       | 27-37-04-09    |
| eClass | 7.1     | 27-37-04-09    |
| eClass | 8       | 27-37-04-09    |
| eClass | 9       | 27-37-04-09    |
| eClass | 9.1     | 27-37-04-09    |
| ETIM   | 5       | EC000228       |
| ETIM   | 6       | EC000228       |
| ETIM   | 7       | EC000228       |
| UNSPSC | 15      | 39-12-16-01    |