

Selector switch, metal Maintained, short lever 1NC + 1NO left, 1NC + 1NO right 4 Position , H Cam Complete device white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)

| Enclosure                                    |                             |
|----------------------------------------------|-----------------------------|
| Number of command points                     | 1                           |
| Delivery state                               |                             |
| • as a kit                                   | No                          |
| Actuator                                     |                             |
| Material of the actuating element            | plastic                     |
| Number of contact modules                    | 4                           |
| Type of unlocking device                     | rotate-to-unlatch mechanism |
| Number of switching positions                | 4                           |
| Front ring                                   |                             |
| Product component front ring                 | Yes                         |
| Design of the front ring                     | standard                    |
| Material of the front ring                   | metal                       |
| General technical data                       |                             |
| Product function                             |                             |
| • positive opening                           | Yes                         |
| Product component                            |                             |
| • Light source                               | No                          |
| Insulation voltage                           |                             |
| • rated value                                | 600 V                       |
| Protection class IP                          | IP66                        |
| • of the terminal                            | IP20                        |
| Operating frequency maximum                  | 600 1/h                     |
| Thermal current                              | 10 A                        |
| Auxiliary circuit                            |                             |
| Number of NC contacts for auxiliary contacts | 2                           |
| Number of NO contacts for auxiliary contacts | 2                           |
| Operating current at AC-15                   |                             |
| • at 110 V rated value                       | 60 A                        |
| • at 230 V rated value                       | 30 A                        |
| • at 400 V rated value                       | 15 A                        |
| • at 500 V rated value                       | 12 A                        |
| Connections/ Terminals                       |                             |

|                                                |                      |
|------------------------------------------------|----------------------|
| Type of electrical connection                  | screw-type terminals |
| Tightening torque of the screws in the bracket | 20 N·m               |
| Tightening torque [lbf·in]                     |                      |
| • with screw-type terminals                    | 8 lbf·in             |

#### Ambient conditions

|                     |                |
|---------------------|----------------|
| Ambient temperature |                |
| • during operation  | -35 ... +70 °C |
| • during storage    | -40 ... +85 °C |

#### Installation/ mounting/ dimensions

|                                   |       |
|-----------------------------------|-------|
| Shape of the installation opening | round |
|-----------------------------------|-------|

#### Certificates/ approvals

#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SA2HABJ2K2>

##### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SA2HABJ2K2>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SA2HABJ2K2>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:52SA2HABJ2K2&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SA2HABJ2K2&lang=en)

last modified:

02/06/2020