

Metal NEMA 4X, selector switch Maintained, short lever Position, B  
Cam 3 position Operator only white insert Non-Illuminated UL file  
E22655 in Vol. 6 (7) Sec. 13 (2)



Figure similar

|                                                                         |                             |
|-------------------------------------------------------------------------|-----------------------------|
| Design of the product                                                   | Actuator round              |
| Enclosure                                                               |                             |
| Number of command points                                                | 1                           |
| Delivery state <ul style="list-style-type: none"><li>as a kit</li></ul> | No                          |
| Actuator                                                                |                             |
| Design of the operating mechanism                                       | selector switch             |
| Material of the actuating element                                       | plastic                     |
| Type of unlocking device                                                | rotate-to-unlatch mechanism |
| Number of switching positions                                           | 3                           |
| Front ring                                                              |                             |
| Product component front ring                                            | Yes                         |
| Design of the front ring                                                | standard                    |
| Material of the front ring                                              | metal                       |
| Color of the front ring                                                 | black                       |
| Holder                                                                  |                             |

|                        |       |
|------------------------|-------|
| Material of the holder | Metal |
|------------------------|-------|

## General technical data

|                             |         |
|-----------------------------|---------|
| Product component           |         |
| • Light source              | No      |
| Degree of pollution         | 1       |
| Protection class IP         | IP66    |
| Operating frequency maximum | 600 1/h |

## Ambient conditions

|                     |                |
|---------------------|----------------|
| Ambient temperature |                |
| • during operation  | -35 ... +70 °C |
| • during storage    | -40 ... +85 °C |

## Installation/ mounting/ dimensions

|                                   |       |
|-----------------------------------|-------|
| Shape of the installation opening | round |
|-----------------------------------|-------|

## Certificates/ approvals

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SX2BAB>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SX2BAB>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SX2BAB>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:52SX2BAB&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SX2BAB&lang=en)

last modified:

03/09/2020