

Metal, keyed selector switch Spring return left & right 1NO-1NC left position ,C Cam Key type 501CH (standard) Key removable center position 3 position Complete device UL file E22655 in Vol. 6 (7) Sec. 13 (2)



Figure similar

Product brand name	SIEMENS Pilot Devices
Design of the product	Complete unit round
Enclosure	
Number of command points	1
Delivery state	No
• as a kit	
Actuator	
Design of the operating mechanism	Key-operated switch
Product extension optional Light source	No
Color	
• of the actuating element	chrome
Material of the actuating element	metal
Number of contact modules	1
Type of unlocking device	without
Number of switching positions	3
Switch position for key distraction	center
Lock make	ILLINOIS

Key number	501CH
-------------------	-------

Front ring

Product component front ring	Yes
Design of the front ring	standard
Material of the front ring	metal
Color of the front ring	chrome

Holder

Material of the holder	Metal
-------------------------------	-------

General technical data

Product function	
<ul style="list-style-type: none"> • positive opening 	Yes
Product component	
<ul style="list-style-type: none"> • Light source 	No
Insulation voltage	
<ul style="list-style-type: none"> • rated value 	600 V
Degree of pollution	1
Type of voltage	
<ul style="list-style-type: none"> • of the operating voltage 	AC/DC
Surge voltage resistance rated value	4 kV
Protection class IP	IP66
<ul style="list-style-type: none"> • of the terminal 	IP20
Vibration resistance	
<ul style="list-style-type: none"> • acc. to IEC 60068-2-6 	0 ... 2000 Hz, 1.52 mm displacement (peak-to-peak) max./ 10g max.
Operating frequency maximum	600 1/h
Thermal current	10 A
Operating voltage	
<ul style="list-style-type: none"> • at AC <ul style="list-style-type: none"> — at 60 Hz rated value • at DC rated value 	5 ... 600 V 5 ... 600 V

Power Electronics

Contact reliability	one incorrect switching operation of 100 million switching operations (5 V, 1 mA)
----------------------------	---

Auxiliary circuit

Number of NC contacts for auxiliary contacts	1
Number of NO contacts for auxiliary contacts	1
Operating current at AC-15	
<ul style="list-style-type: none"> • at 110 V rated value • at 230 V rated value • at 400 V rated value • at 500 V rated value 	60 A 30 A 15 A 12 A

Connections/ Terminals

Type of electrical connection	screw-type terminals
Type of connectable conductor cross-sections <ul style="list-style-type: none">• at AWG conductors for auxiliary contacts	1x (18 ... 12), 2x (18 ... 16), 2x (16 ... 14), 2x 12
Tightening torque of the screws in the bracket	20 N·m
Tightening torque [lbf·in] <ul style="list-style-type: none">• with screw-type terminals	8 lbf·in

Safety related data

Protection against electrical shock	finger-safe
--	-------------

Ambient conditions

Ambient temperature <ul style="list-style-type: none">• during operation• during storage	-35 ... +70 °C -40 ... +85 °C
--	----------------------------------

Installation/ mounting/ dimensions

Shape of the installation opening	round
--	-------

Certificates/ approvals

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SC6CVA1>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SC6CVA1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SC6CVA1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SC6CVA1&lang=en

last modified:

02/19/2020