



Siemens Low Voltage Circuit Protection Heavy Duty Safety Switches.
 Type: ENCLOSED, SAFETY SWITCH Std: UL V. Rating: 600V A.
 Rating: 60A Wattage: 4W No. Of Poles: 3P F. Rating: 60Hz Action:
 SINGLE THROW Material: STEEL Enclosure: TYPE 1. 2-3 point
 mounting holes. O. Cycles: 10000 O. Temperature: (-20F-120F)
 AMBIENT TEMPERATURE Environmental Conditions: INDOOR

| | |
|--|-----------------------------|
| Installation location | INDOOR |
| Manner of function of the actuating element | SINGLE THROW |
| Mechanical service life (switching cycles) typical | 10000 |
| Mounting type | 2 OR 3 POINT MOUNTING HOLES |
| Number of poles | 3 |

| Electricity | |
|---|-------|
| Ampacity | 60 A |
| Supply voltage frequency rated value 50/60 Hz | Yes |
| Voltage between phase and phase rated value | 600 V |

| Switching capacity | |
|---------------------------------|-----|
| Switching capacity active power | 4 W |

| Environmental conditions | |
|--|--------|
| Ambient temperature during operation maximum | 120 °C |
| Ambient temperature during operation minimum | -20 °C |

| Model | |
|--------------------------|------------------------|
| Product brand name | SIEMENS |
| Product type designation | ENCLOSED/SAFETY SWITCH |

Mechanical Design

Design of the housing TYPE 1

Material STEEL

General product approval

Certificate of suitability UL

last modified: 05/28/2019