



ENGLISH

Constant Current LED Driver 14.5-28.5vdc 30 Watt



The RS Pro Range of 30watt Constant current LED Drivers are housed in a compact light weight high quality IP20 plastic enclosure with covered input & output terminals suitable for general Indoor LED applications

Features:

- Input Voltage 90-305vac
- IP20 Rated
- Low Profile
- Compact Plastic Low Profile enclosure
- 1 Year Warranty
- CE Approved







ENGLISH

	0.10.11
Specification	
Part Number	1766763
Output Voltage Rating	1428.5VDC
Output Current Range	1050mA
Rated Power	30W
Dimensions	77 x 79.5 x 25mm
Input Voltage Range	90-305VAC
Input Voltage Frequency	47-60Hz
Inrush Current	70A/230V (25°C)
Efficiency	>87%
Power Consumption Without Load	55V max
Overload Protection	105 \sim 1.2 TIMES RATED LOAD (AUTOMATICALLY RECOVER
Short Circuit Protection	HICCUP MODE, RECOVERS AUTOMATICALLY AFTER FAULT CONDITIONS IS REMOVED
Automatically Restart	Yes
Working Temperature	-40°C~70°C
Relative Humidity	15%~95%
МТВБ	50000hr
EMC emission	EN55015
EMC Immunity	EN6100-3-2, EN61547
Safety Standards	EN61347-1, EN61347-2-13