




**Datasheet**  
**Stock No. 190-2817, 190-2818, 190-2819,**  
**190-2820, 190-2821, 190-2822**  
**RS PRO LIGHT MODULE ELLIPTICAL**  
**LIGHT TOWER**



**ENGLISH**



*Led luminous module.*

<b>DOME</b>	PC																		
<b>GASKET</b>	O-Ring Silicone																		
<b>LUMINOUS SOURCE</b>	N°6 LED																		
<b>AVAILABLE COLOURS</b>	<div style="display: flex; flex-direction: column; gap: 5px;"> <div style="display: flex; align-items: center;"><span style="width: 15px; height: 15px; border: 1px solid black; background-color: white; margin-right: 5px;"></span> 1902822</div> <div style="display: flex; align-items: center;"><span style="width: 15px; height: 15px; background-color: orange; margin-right: 5px;"></span> 1902818</div> <div style="display: flex; align-items: center;"><span style="width: 15px; height: 15px; background-color: yellow; margin-right: 5px;"></span> 1902821</div> <div style="display: flex; align-items: center;"><span style="width: 15px; height: 15px; background-color: red; margin-right: 5px;"></span> 1902819</div> <div style="display: flex; align-items: center;"><span style="width: 15px; height: 15px; background-color: blue; margin-right: 5px;"></span> 1902817</div> <div style="display: flex; align-items: center;"><span style="width: 15px; height: 15px; background-color: green; margin-right: 5px;"></span> 1902820</div> </div>																		
<b>VOLTAGE</b>	12 Vdc/Vac - 24 Vdc/Vac - 120/240 Vac																		
<b>OPERATION</b>	∞																		
<b>CURRENT CONSUMPTION</b>		12 Vdc	12 Vac	24 Vdc	24 Vac	120 Vac	240 Vac												
	Steady conn. base (mA)	40	60	35	75	30	25												
	Multi-function conn. base (mA)	55	120	50	110	30	25												
<b>LIGHT OUTPUT</b>	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="width: 20px; height: 20px; background-color: white;"></td> <td style="width: 20px; height: 20px; background-color: yellow;"></td> <td style="width: 20px; height: 20px; background-color: orange;"></td> <td style="width: 20px; height: 20px; background-color: green;"></td> <td style="width: 20px; height: 20px; background-color: red;"></td> <td style="width: 20px; height: 20px; background-color: blue;"></td> </tr> <tr> <td style="text-align: center;">10</td> <td style="text-align: center;">8</td> <td style="text-align: center;">3</td> <td style="text-align: center;">5</td> <td style="text-align: center;">3</td> <td style="text-align: center;">1</td> </tr> </table>													10	8	3	5	3	1
10	8	3	5	3	1														

These data are disclosed only for information purposes. Sirena S.p.A. reserves the right to modify them at any time without prior notice.

<b>LIGHT EFFECT</b>	Steady/Flashing
<b>FLASHES PER MINUTE</b>	1F X 75, 2F X 90, 3F X 72, 5F X 70
<b>IP RATING</b>	IP66
<b>OPERATING TEMPERATURE</b>	-30°C+50°C
<b>VIBRATIONS</b>	INDUSTRIAL CEI 60068-2-6 SINE
<b>CERTIFICATIONS, APPROVALS</b>	CE
<b>MOUNTING</b>	Stackable
<b>TECHNICAL DRAWING</b>	