

Product availability: Non-Stock - Not normally stocked in distribution facility



Complementary

Control Circuit Type	Common control circuit
Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Line Rated Current	18 A
Number of Poles	3
Horsepower Rating	3 Hp 200...230 V AC, 3 phase 5 hp 460/575 V AC, 3 phase
Maximum Voltage Rating	600 V AC
Control Units	No control units
Disconnect Type	Non-fusible disconnect
Thermal overload type	Melting alloy
Protection type	Overload
Device mounting	Surface
Electrical connection	Screw terminal
NEMA size	0
Height	24.13 in (613 mm)
Width	20.51 in (521 mm)
Depth	8.70 in (221 mm)


Environment

NEMA Rating	NEMA 1
Enclosure type	Standard environment enclosure indoor installation
Product certifications	UL listed NEMA

Ordering and shipping details

Category	21401 - 8941 DUPLEX MOTOR CONTROLLERS
Discount Schedule	CP1
GTIN	00785901769743
Package weight(Lbs)	26.31 kg (58 lb(US))
Returnability	Yes
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------