HOM1224M125PRBVP

Homeline, LC, 125 A, 120/240 V, 1 PH, MB, PoN, 12 SP, N3R, surf, VP



Product availability: Stock - Normally stocked in distribution facility



Main	
Product or component type	Load Center
Marketing Trade Name	Homeline
Load center type	Main breaker
Line Rated Current	125 A
Number of spaces	12
Number of circuits	24
Enclosure Rating	NEMA 3R outdoor
Cover type	Surface cover
Electrical connection	Lugs
Included Options	Circuit breaker 3) 1P 20 A 120/240 V AC Circuit breaker 2) 2P 30 A 120/240 V AC Circuit breaker 1) 2P 125 A 120/240 V AC main sup- ply ready assembled

Complementary

Short-circuit current	22 kA
Number of Tandem Breakers	12
Number of Phases	1 phase
[Ue] rated operational voltage	120/240 V AC
Wire Size	AWG 6AWG 2/0 aluminium AWG 6AWG 1 copper
Wiring configuration	3-wire
Cover finish	Gray baked enamel
Busbar Material	Tin plated aluminium busbar
Enclosure material	Welded galvannealed steel
Surface finish	Baked enamel grey
Box number	3R
Height	18.94 in (481 mm)
Width	14.76 in (375 mm)
Depth	4.53 in (115 mm)

Environment

Ambient air temperature for operation	23 °F (-5 °C) 104 °F (40 °C)	
Product certifications	UL E-6294	

Ordering and shipping details

00185 - MISC. HOM LOAD CENTERS
DE3C
00785901861133
10.89 kg (24 lb(US))
Yes
US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant E EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations