

# Product data sheet

## Characteristics

# SDSA1175T

Surge Protect - 36kA - 120VAC - 1P3W - 25 kA  
- T1

Product availability: Stock - Normally stocked in distribution facility



### Main

Product	Surge protection device
---------	-------------------------

### Complementary

Surge Current	36 kA
Voltage Rating	120 V AC
Number of Phases	1 phase
Wiring Configuration	3-wire
Connection	Wire
MCOV	150 V
Nominal Discharge Current	10 kA
SCCR	25 kA
Local Signalling	Status LED
Height	57.15 mm (2.25 in)
Width	57.15 mm (2.25 in)
Depth	49.15 mm (1.935 in)
Cable length	0.61 m (2 ft)

### Environment

Enclosure Rating	NEMA 1
Enclosure Material	Black plastic
Standards	CSA C22.2 No 8 UL 1449:ed. 4

### Ordering and shipping details

Category	08462 - SURGE PROTECTION SDSA
Discount Schedule	DE1B
GTIN	00785901984092
Package weight(Lbs)	0.30 kg (0.66 lb(US))
Returnability	Yes
Country of origin	MX

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals which are known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
EU RoHS Directive	Not compliant

## Contractual warranty

---

Warranty	18 months
----------	-----------

---

Approximate Dimensions

