

Product availability: Stock - Normally stocked in distribution facility



Main

Range	TeSys
Product name	TeSys U
Device short name	LUB
Product or component type	Non reversing power base
Device application	Motor
Poles description	3P
Suitability for isolation	Yes
[I _{th}] conventional free air thermal current	32 A
Utilisation category	AC-44 AC-43 AC-41
[U _c] control circuit voltage	24 V AC 50/60 Hz 24 V DC 48 V AC 50/60 Hz 48...72 V DC 110...220 V DC 110...240 V AC 50/60 Hz

Complementary

Auxiliary contact composition	1 NO + 1 NC
Auxiliary contacts type	Linked contacts 1 NO + 1 NC) IEC 60947-4-1 Mirror contact 1 NC) state of the power draft IEC 60947-1
[U _e] rated operational voltage	230 V 440 V 500 V 690 V
Network frequency	40...60 Hz
[I _e] rated operational current	21 A 690 V 23 A 500 V 32 A ≤ 440 V
[I _{cs}] rated service breaking capacity	10 KA 500 V 4 KA 690 V 50 KA 230 V 50 KA 440 V
Typical current consumption	200 MA 24 V DC I maximum while closing with LUCM 220 MA 24 V AC I maximum while closing with LUCA, LUCB, LUCC, LUCD 220 MA 24 V DC I maximum while closing with LUCA, LUCB, LUCC, LUCD 25 MA 110...220 V DC I rms sealed with LUCA, LUCB, LUCC, LUCD 25 MA 110...240 V AC I rms sealed with LUCA, LUCB, LUCC, LUCD 280 MA 110...220 V DC I maximum while closing with LUCA, LUCB, LUCC, LUCD 280 MA 110...240 V AC I maximum while closing with LUCA, LUCB, LUCC, LUCD 280 MA 48...72 V AC I maximum while closing with LUCA, LUCB, LUCC, LUCD 280 MA 48...72 V DC I maximum while closing with LUCA, LUCB, LUCC, LUCD 45 MA 48...72 V AC I rms sealed with LUCA, LUCB, LUCC, LUCD 45 MA 48...72 V DC I rms sealed with LUCA, LUCB, LUCC, LUCD 75 MA 24 V DC I rms sealed with LUCM 80 MA 24 V DC I rms sealed with LUCA, LUCB, LUCC, LUCD 90 MA 24 V AC I rms sealed with LUCA, LUCB, LUCC, LUCD
Safety reliability level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Operating time	35 ms opening with LUCA, LUCB, LUCC, LUCD, LUCM control circuit 50 ms >= 72 V closing with LUCA, LUCB, LUCC, LUCD control circuit 60 ms 48 V closing with LUCA, LUCB, LUCC, LUCD control circuit 70 ms 24 V closing with LUCA, LUCB, LUCC, LUCD control circuit 65 ms closing with LUCM control circuit
Mechanical durability	15000000 cycles
Maximum operating rate	60 cyc/mn
[Ui] rated insulation voltage	600 V UL 508 690 V IEC 60947-1 3) 600 V CSA C22.2 No 14
[Uimp] rated impulse withstand voltage	6 kVIEC 60947-6-2
Safe separation of circuit	400 V SELV between the control and auxiliary circuits IEC 60947-1 appendix N 400 V SELV between the control or auxiliary circuit and the main circuit IEC 60947-1 appendix N
Connections - terminals	Control circuit screw clamp terminals 1 0.00...0.00 in ² (0.34...1.5 mm ²) flexible with cable end Control circuit screw clamp terminals 1 0.00...0.00 in ² (0.75...1.5 mm ²) flexible without cable end Control circuit screw clamp terminals 1 0.00...0.00 in ² (0.75...1.5 mm ²) rigid without cable end Control circuit screw clamp terminals 2 0.00...0.00 in ² (0.34...1.5 mm ²) flexible with cable end Control circuit screw clamp terminals 2 0.00...0.00 in ² (0.75...1.5 mm ²) flexible without cable end Control circuit screw clamp terminals 2 0.00...0.00 in ² (0.75...1.5 mm ²) rigid without cable end Power circuit screw clamp terminals 1 0.00...0.02 in ² (1...10 mm ²) rigid without cable end Power circuit screw clamp terminals 1 0.00...0.01 in ² (1...6 mm ²) flexible with cable end Power circuit screw clamp terminals 1 0.00...0.02 in ² (2.5...10 mm ²) flexible without cable end Power circuit screw clamp terminals 2 0.00...0.01 in ² (1...6 mm ²) flexible with cable end Power circuit screw clamp terminals 2 0.00...0.01 in ² (1...6 mm ²) rigid without cable end Power circuit screw clamp terminals 2 0.00...0.01 in ² (1.5...6 mm ²) flexible without cable end
Tightening torque	Control circuit 7.08...10.62 lbf.in (0.8...1.2 N.m) flat 0.20 in (5 mm) Control circuit 7.08...10.62 lbf.in (0.8...1.2 N.m) Philips no 1 0.20 in (5 mm) Power circuit 16.82...22.13 lbf.in (1.9...2.5 N.m) flat 0.24 in (6 mm) Power circuit 16.82...22.13 lbf.in (1.9...2.5 N.m) Philips No 2 0.24 in (6 mm)
Width	1.77 in (45 mm)
Height	6.06 in (154 mm)
Depth	4.96 in (126 mm)
Net weight	1.98 lb(US) (0.9 kg)

Environment


Heat dissipation	3 W control circuit with LUCA, LUCB, LUCC, LUCD 1.8 W control circuit with LUCM
Immunity to microbreaks	3 ms
Immunity to voltage dips	70 % / 500 ms IEC 61000-4-11
Product certifications	LROS (Lloyds register of shipping) CCC ABS CSA ASEFA UL GL GOST ATEX BV DNV
Standards	UL 508 type E, with phase barrier EN 60947-6-2 IEC 60947-6-2 CSA C22.2 No 14 type E
IP degree of protection	IP20 IEC 60947-1 front panel and wired terminals) IP20 IEC 60947-1 other faces) IP40 IEC 60947-1 front panel outside connection zone)
Protective treatment	TH IEC 60068

Ambient air temperature for operation	-13...140 °F (-25...60 °C) with LUCM -13...158 °F (-25...70 °C) with LUCA, LUCB, LUCC, LUCD
Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Fire resistance	1760 °F (960 °C) parts supporting live components IEC 60695-2-12 1202 °F (650 °C) IEC 60695-2-12
Operating altitude	6561.68 ft (2000 m)
Shock resistance	10 gn power poles open IEC 60068-2-27 15 gn power poles closed IEC 60068-2-27
Vibration resistance	2 gn 5...300 Hz) power poles open IEC 60068-2-27 4 gn 5...300 Hz) power poles closed IEC 60068-2-27
Resistance to electrostatic discharge	8 kV 3 in open air IEC 61000-4-2 8 kV 4 on contact IEC 61000-4-2
Resistance to radiated fields	9.14 V/m (10 V/m) 3 IEC 61000-4-3
Resistance to fast transients	2 kV 3 serial link IEC 61000-4-4 4 kV 4 all circuits except for serial link IEC 61000-4-4
Non-dissipating shock wave	1 kV serial mode 24...240 V AC IEC 60947-6-2 1 kV serial mode 48...220 V DC IEC 60947-6-2 2 kV common mode 24...240 V AC IEC 60947-6-2 2 kV common mode 48...220 V DC IEC 60947-6-2
Immunity to radioelectric fields	10 V IEC 61000-4-6

Ordering and shipping details

Category	22396 - TESYS U - SELF PRCTD STARTER (LUB)
Discount Schedule	I11
GTIN	00785901221814
Package weight(Lbs)	0.90 kg (1.98 lb(US))
Returnability	Yes
Country of origin	FR

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------