

Product availability: Stock - Normally stocked in distribution facility



### Main

|                           |                   |
|---------------------------|-------------------|
| Range                     | TeSys             |
| Device short name         | GVAU              |
| Product or component type | Undervoltage trip |

### Complementary

|                                 |  |
|---------------------------------|--|
| Product compatibility           | GV2P<br>GV3L<br>GV2LE<br>GV3P<br>GV2ME<br>GV2L   |
| [Uc] control circuit voltage    | 380...400 V AC 50 Hz   |
| Control circuit voltage limits  | 0.85...1.1 Un  |
| [Ui] rated insulation voltage   | 600 V AC UL 508<br>690 V AC IEC 60947-1<br>600 V AC CSA C22.2 No 14  |
| Threshold tripping voltage      | 0.7...0.35 Un  |
| Inrush power in VA              | 12 VA AC   |
| Inrush power in W               | 8 W DC   |
| Hold-in power consumption in VA | 3.5 VA AC  |
| Hold-in power consumption in W  | 1.1 W DC   |
| Operating time                  | 10...15 ms IEC 60947-1   |
| On-load factor                  | 100 %  |
| Connections - terminals         | Screw clamp terminals 1 0.00...0.00 in <sup>2</sup> (0.75...2.5 mm <sup>2</sup> )flexible without cable end<br>Screw clamp terminals 1 0.00...0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )solid<br>Screw clamp terminals 2 0.00...0.00 in <sup>2</sup> (0.75...2.5 mm <sup>2</sup> )flexible without cable end<br>Screw clamp terminals 2 0.00...0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )solid<br>Screw clamp terminals 1 0.00...0.00 in <sup>2</sup> (0.75...1.5 mm <sup>2</sup> )flexible with cable end<br>Screw clamp terminals 2 0.00...0.00 in <sup>2</sup> (0.75...1.5 mm <sup>2</sup> )flexible with cable end |
| Tightening torque               | < 1.4 N.m screw clamp terminals  |
| Mechanical durability           | 10000 Cycles with GV3P and GV3L<br>30000 cycles with GV2ME and GV2P  |
| Quantity per set                | Set of 10  |
| Net weight                      | 0.23 lb(US) (0.105 kg)   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Ordering and shipping details

|                     |                                    |
|---------------------|------------------------------------|
| Category            | 22367 - MANUAL STR PROTECTOR - GV2 |
| Discount Schedule   | I11                                |
| GTIN                | 00785901212546                     |
| Package weight(Lbs) | 0.11 kg (0.25 lb(US))              |
| Returnability       | Yes                                |
| Country of origin   | CZ                                 |

## Offer Sustainability

|                            |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product  |
| REACH Regulation           | <a href="#">REACH Declaration</a>  |
| REACH free of SVHC         | Yes  |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>  |
| Toxic heavy metal free     | Yes  |
| Mercury free               | Yes  |
| RoHS exemption information | <a href="#">Yes</a>  |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>  |
| Circularity Profile        | No need of specific recycling operations   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---

---

GVAU...

