

Product availability: Non-Stock - Not normally stocked in distribution facility



### Main

Range of product	Harmony XAR
Product or component type	Base station
Device short name	ZARB
Product specific application	Hoisting applications Material handling

### Complementary

Connector type	Industrial socket
Cable entry	Cable gland
Material	PC (polycarbonate)
[Us] rated supply voltage	24...48 V AC/DC
Vibration resistance	0.075 mm 10...55 Hz)
Shock resistance	15 gn 11 ms
Provided equipment	Internal antenna
Nominal output current	0.54 A 48 V AC IEC 60947-5-1
Number of relays	18
Relay type	Motion relay outputs 9 NO Auxiliary relay outputs 7 NO Auxiliary relay outputs 2 NC + 2 NO
Safety outputs	2 NC relay outputs
Switching capacity in VA	5 VA DC 26 VA AC
Maximum switching current	6.8 mA
Maximum switching voltage	48 V AC/DC +/- 20 %)
Communication network type	Wireless bluetooth low energy
Transmission frequency	2.4 GHz
Maximum sensing distance	328.08 ft (100 m) in free field
Number of channels	40
Fixing mode	4 holes
Electrical durability	100000 cycles
Mechanical durability	1000000 cycles
Number of alarms	6 programmable alarms
Number of inputs	12
Service life	10 year(s)
Width	11.02 in (280 mm)
Height	12.01 in (305 mm)
Depth	3.94 in (100 mm)
Product weight	3.20 lb(US) (1.45 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

IP degree of protection	IP65
NEMA degree of protection	NEMA 4
Pollution degree	3
Electromagnetic compatibility	Resistance to electrostatic discharge 4 kV on contact)class B IEC 61000-4-2 Resistance to electrostatic discharge 8 kV in air)class B IEC 61000-4-2 Resistance to radiated electromagnetic fields 10 V/mclass B IEC 61000-4-3
Standards	IEC 61000-6-2
Radio agreement	SRRC ICASA ANATEL RSS ARIB FCC
Relative humidity	0...97 %
Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Product certifications	CSA EAC UL KC CE C-Tick
Environmental characteristic	RoHS compliant

## Ordering and shipping details

Category	22479 - EXL HOIST WIRELESS PENDANT & ACC
Discount Schedule	CS2
GTIN	00785901780960
Package weight(Lbs)	1.81 kg (4 lb(US))
Returnability	No
Country of origin	FR

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds and Di-isodecyl phthalate (DIDP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Dimensions

