

Product availability: Stock - Normally stocked in distribution facility



### Main

Product or component type	Ethernet unmanaged switch
---------------------------	---------------------------

### Complementary

Range compatibility	Modicon M251 Modicon M241
Product compatibility	Modicon M241 logic controller Modicon M251 logic controller
Current consumption	360 mA 5 V DC communication bus
Integrated connection type	Ethernet 4 RJ45
Transmission rate	10/100 Mbit/s
Port Ethernet	10BASE-T/100BASE-TX - 4 copper cable
Web services	Web server
Communication service	Modbus TCP server Modbus TCP slave device FTP NGVL Monitoring IEC VAR ACCESS Programming SNMP Modbus TCP client Downloading Updating firmware Ethernet/IP slave device DHCP client
Maximum number of connections	8 Modbus server 16 Ethernet/IP device
Communication port protocol	Ethernet IP/Modbus TCP TCP (Transmission Control Protocol) UDP (User Datagram Protocol) SNMP
Redundancy	No
Local signalling	PWR 1 LED green) Ethernet link 1 LED per channel green/yellow) Ethernet port activity 1 LED per channel green)
Electrical connection	RJ45 4 connectors for connecting Ethernet network Screw connector terminal for connecting the functional ground
Marking	CE

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Surge withstand	1 KV power lines (DC) common mode EN/IEC 61000-4-5 2 KV power lines (AC) common mode EN/IEC 61000-4-5 2 KV relay output common mode EN/IEC 61000-4-5 1 KV I/O common mode EN/IEC 61000-4-5 1 KV shielded cable common mode EN/IEC 61000-4-5 0.5 KV power lines (DC) differential mode EN/IEC 61000-4-5 1 KV power lines (AC) differential mode EN/IEC 61000-4-5 1 KV relay output differential mode EN/IEC 61000-4-5 0.5 kV I/O differential mode EN/IEC 61000-4-5
Mounting support	Top hat type TH35-15 rail IEC 60715 Top hat type TH35-7.5 rail IEC 60715 Plate or panel with fixing kit
Width	0.98 in (25 mm)
Height	3.54 in (90 mm)
Depth	3.54 in (90 mm)
Net weight	0.28 lb(US) (0.125 kg)

## Environment

Standards	UL 508 EN/IEC 61131-2
Product certifications	CULus C-Tick
Resistance to electrostatic discharge	8 KV in air EN/IEC 61000-4-2 4 KV on contact EN/IEC 61000-4-2 8 KV in air Marine specification (LR, ABS, DNV, GL) 6 KV on contact Marine specification (LR, ABS, DNV, GL)
Resistance to electromagnetic fields	9.14 V/m (10 V/m) 80 MHz...1 GHz EN/IEC 61000-4-3 2.74 V/m (3 V/m) 1.4 GHz...2 GHz EN/IEC 61000-4-3 0.91 V/m (1 V/m) 2...2.7 GHz EN/IEC 61000-4-3
Resistance to fast transients	2 KV EN/IEC 61000-4-4 power lines) 2 KV EN/IEC 61000-4-4 relay output) 1.5 KV EN/IEC 61000-4-4 I/O) 1 KV EN/IEC 61000-4-4 Ethernet line) 1 kV EN/IEC 61000-4-4 serial link)
Resistance to conducted disturbances	10 V 0.15...80 MHz EN/IEC 61000-4-6 3 V 0.1...80 MHz Marine specification (LR, ABS, DNV, GL) 10 V spot frequency (2, 3, 4, 6.2, 8.2, 12.6, 16.5, 18.8, 22, 25 MHz) Marine specification (LR, ABS, DNV, GL)
Electromagnetic emission	Conducted emissions 79 dB $\mu$ V/m QP/66 dB $\mu$ V/m AV power lines (AC))0.15... 0.5 MHz EN/IEC 55011 Conducted emissions 73 dB $\mu$ V/m QP/60 dB $\mu$ V/m AV power lines (AC))0.5... 300 MHz EN/IEC 55011 Conducted emissions 120...69 dB $\mu$ V/m QP power lines)10...150 kHz EN/IEC 55011 Conducted emissions 63 dB $\mu$ V/m QP power lines)1.5...30 MHz EN/IEC 55011 Radiated emissions 40 dB $\mu$ V/m QP class A30...230 MHz EN/IEC 55011 Radiated emissions 60...54 dB $\mu$ V/m QP30...100 MHz Marine specification (LR, ABS, DNV, GL) Radiated emissions 24 dB $\mu$ V/m QP156...165 MHz Marine specification (LR, ABS, DNV, GL) Conducted emissions 79...63 dB $\mu$ V/m QP power lines)150...1500 kHz EN/IEC 55011 Radiated emissions 47 dB $\mu$ V/m QP class A230...1000 MHz EN/IEC 55011 Radiated emissions 80...50 dB $\mu$ V/m QP150...30000 kHz Marine specification (LR, ABS, DNV, GL) Radiated emissions 54 dB $\mu$ V/m QP100...2000 MHz Marine specification (LR, ABS, DNV, GL)
Ambient air temperature for operation	14...131 °F (-10...55 °C) horizontal installation 14...122 °F (-10...50 °C) vertical installation
Ambient air temperature for storage	-13...158 °F (-25...70 °C)
Relative humidity	10...95 %, without condensation in operation) 10...95 %, without condensation in storage)
IP degree of protection	IP20 with protective cover in place
Pollution degree	2
Operating altitude	0...6561.68 ft (0...2000 m)
Storage altitude	0.00...9842.52 ft (0...3000 m)

Vibration resistance	1 mm 5...13.2 Hz symmetrical rail 3 gn 8.7...150 Hz symmetrical rail 1 mm 5...13.2 Hz panel mounting 0.7 gn 13.2...100 Hz panel mounting
Shock resistance	15 gn 11 ms

### Ordering and shipping details

Category	22533 - M2XX PLC & ACCESSORIES
Discount Schedule	MSX
GTIN	00785901098232
Package weight(Lbs)	0.21 kg (0.46 lb(US))
Returnability	Yes
Country of origin	ID

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.