



Product availability: Stock - Normally stocked in distribution facility



Main

| | |
|------------------------------|---|
| Product | Miniature circuit-breaker |
| Range | Homeline |
| Current Rating | 20 A 50 A |
| Certifications | UL listed |
| Voltage Rating | 120/240 V AC |
| Mounting Type | Plug-in |
| Number of Poles | 2P 1P |
| Short Circuit Current Rating | 10 kA |
| Number of Spaces | 2 |
| Circuit Breaker Type | Quad tandem |
| Ratings | HACR rated |
| Electrical Connection | Box lugs |
| Wire Size | AWG 14...AWG 6 copper)1 AWG 12...AWG 6 aluminium)1 AWG 12...AWG 8 aluminium)1 |
| Type of packing | Consumer packaging |

Complementary

| | |
|-------------------|---|
| Height | 79.50 mm (3.13 in) |
| Width | 50.80 mm (2 in) |
| Depth | 75.69 mm (2.98 in) |
| Tightening torque | 35.40 Lbf.in (4.0 N.m) 0.00...0.02 in ² (2.5...10 mm ²) AWG 16...AWG 14) 35.40 lbf.in (4.0 N.m) 0.01...0.03 in ² (4...20 mm ²) AWG 12...AWG 4) |

Environment

| | |
|---------------------------------------|----------------|
| Ambient air temperature for operation | 104 °F (40 °C) |
|---------------------------------------|----------------|

Ordering and shipping details

| | |
|---------------------|------------------------------------|
| Category | 00046 - HOM/T 15-30A 1P; 15-60A 2P |
| Discount Schedule | DE3D |
| GTIN | 00785901394006 |
| Package weight(Lbs) | 0.39 kg (0.85 lb(US)) |
| Returnability | Yes |
| Country of origin | MX |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |

| | |
|-----------------------------|---|
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| Contractual warranty | |
| Warranty | 18 months |