Product availability: Non-Stock - Not normally stocked in distribution facility



Main	
Product or component type	Controllers separate parts
Accessory / separate part category	Control accessories
Product specific application	Heavy hoisting applications Light hoisting applications Medium hoisting applications
Product compatibility	XKD XKM XKB
Accessory / separate part type	Potentiometer
Condition of use	For standard applications
Ohmic value	2200 Ohm
Size	15 mm

#### Complementary

Standards	UTE 93-265	
Potentiometer characteristic	Linear function Continuous rotational operation	
Operating angle	360 °	
Mechanical durability	3000000 cycles	
Centre tap	Wired out to terminal	
Centre tap dead zone	2 ° +/- 1 %	
Power dissipation in W	3 W 185 °F (85 °C)	
Connections - terminals	Flying leads from soldered standard tags	
Product weight	0.13 lb(US) (0.06 kg)	

#### Environment

Mounting mode	By the body

### Ordering and shipping details

Category	22474 - PUSHBUTTON, CRANE JOYSTICKS	
Discount Schedule	Ţ	
GTIN	03389110929973	
Package weight(Lbs)	0.06 kg (0.14 lb(US))	
Returnability	No	
Country of origin	FR	

# Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEU RoHS Declaration
China RoHS Regulation	☐ China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

Warranty	18 months