

Product availability: Stock - Normally stocked in distribution facility



Main

Range of product	Altivar
Product or component type	Communication module

Complementary

Range compatibility	Altivar 32 Altivar Machine ATV340 except Sercos drives Altivar Easy 610 Lexium 32 Altivar Process ATV900 Altivar Process ATV600 Altivar Machine ATV320 Altivar Process Modular
Product compatibility	Lexium 32
Communication port protocol	Profibus DP V1
Electrical connection	1 female connector SUB-D 9
Transmission rate	9.6 kbps...12 Mbps
Addressing	1...126 configurable by graphic terminal/SoMove software Configuration settings
Communication service	4 configurable telegrams Mapping of the process data from the master Parameters management compliant with PROFIdrive V4.1 Several DP V1 messaging modes Drive profile native ATV32 IEC 61800-7-201 (CiA 402)
Display type	1 LED RUN 1 LED bus fault (BF)
Diagnostic function	Diagnostic data with VSD status Host drive handled from two masters (MS0 and MS1) Standard identification and maintenance requests
Bus profile	PROFIdrive CiA 402

Environment

Standards	IEC 61800-7-201 (CiA 402)
-----------	---------------------------

Ordering and shipping details

Category	18263 - LEXIUM 32 ACCESSORIES
Discount Schedule	PC51
GTIN	00785901952886
Package weight(Lbs)	0.06 kg (0.14 lb(US))
Returnability	Yes
Country of origin	CN

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------