



Product availability: Non-Stock - Not normally stocked in distribution facility



### Main

Product	Single Throw Safety Switch
Current Rating	30 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 4X fiberglass reinforced polyester
Factory Installed Neutral	None
Disconnect Type	Fusible disconnect
Short Circuit Current Rating	10 KA H or K 200 kA R, J or L
Mounting Type	Surface
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	Heavy duty
Voltage Rating	600 V AC/DC
Wire Size	AWG 12...AWG 6 aluminium AWG 14...AWG 6 copper

### Complementary

Width	279.40 mm (11 in)
Height	419.10 mm (16.5 in)
Depth	223.52 mm (8.8 in)
Tightening torque	5.08 N.M (45 lbf.in) 0.02 in <sup>2</sup> (13.3 mm <sup>2</sup> ) AWG 6) 4.52 N.M (40 lbf.in) 0.01 in <sup>2</sup> (8.367 mm <sup>2</sup> ) AWG 8) 3.95 N.m (35 lbf.in) 0.00...0.01 in <sup>2</sup> (2.06...5.261 mm <sup>2</sup> ) AWG 14...AWG 10)

### Ordering and shipping details

Category	00111 - H&HU SW,N4X(DF,DX)NON-MET
Discount Schedule	DE1
GTIN	00785901627845
Package weight(Lbs)	9.51 kg (20.96 lb(US))
Returnability	Yes
Country of origin	MX

### Offer Sustainability

Sustainable offer status	Green Premium product
RECh Regulation	<a href="#">RECh Declaration</a>
RECh free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Contractual warranty

---

Warranty

18 months

---