3090SCCT032

Square D - PowerLogic 3090 SCCT - split core CT - 300/5 A - size 2 - 2.5 VA

Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Range	PowerLogic
Product or component type	Current transformer
Accessory / separate part category	Measurement accessory

Complementary

Range compatibility	PowerLogic PM3000 power meter PowerLogic PM5000 power meter PowerLogic PM8000 power meter	
	PowerLogic ION7400 power meter	
	CM4000T circuit monitor	
	Acti 9 iEM3000 energy meter	
Current transformer type	Split core	
Primary operational current	300 A	
Secondary current	5 A	
Network type	AC	
Network frequency	50/60 Hz	
Current transformer ratio	300/5	
Burden	2.5 VA	
Electrical connection	5.91 ft (1.8 m) AWG 18 flying leads	
Insulation	Basic insulation 600 V AC	
	Reinforced insulation 300 V AC	
Measurement accuracy	1 % full scale	
Mounting location	Indoor use only	
Width	Internal 1.26 in (32 mm)	
	External 4.76 in (121 mm)	
Depth	1.14 in (29 mm)	
Height	Internal 1.50 in (38 mm)	
	External 4.21 in (107 mm)	

Environment

Relative humidity	095 % non-condensing	
Installation category	III	
Pollution degree	2	
Ambient air temperature for operation	5140 °F (-1560 °C)	
Ambient air temperature for storage	-40158 °F (-4070 °C)	
Operating altitude	<= 9842.52 ft (3000 m)	
Standards	UL 1015	
	IEC 61010-1	
	UL 61010-1	

Ordering and shipping details

Category	09661 - POWERLOGIC BASIC CTS
Discount Schedule	PL1
GTIN	00785901000457
Package weight(Lbs)	0.45 kg (1 lb(US))
Returnability	No
Country of origin	US

Contractual warranty

Warranty 18 months	
--------------------	--