

Product availability: Non-Stock - Not normally stocked in distribution facility



## Main

Product range	9050A/H
Product type	Timer
Timing mode	On-delay
Timing range	0.1 s...1 min
Switch function	SPDT
Coil voltage	120 V AC 60 Hz 110 V AC 50 Hz
Contact operation	Time delayed 1 NO + 1 NC
Current rating	15 A

## Complementary

Maximum switching voltage	600 V AC
Electrical connection	Screw-clamp terminals
Reset response time	29 Ms - on-delay 27 ms - off-delay
Mounting support	Panel

## Environment

Ambient temperature range - operational	20...40 °C (68...104 °F)
Certifications	UL listed CSA
Height	2.64 in (67 mm)
Width	4.02 in (102 mm)
Depth	4.37 in (111 mm)

## Ordering and shipping details

Category	21631 - 9050 A ONE MINUTE PNEUMATIC TIMER
Discount Schedule	CP1
GTIN	00785901864318
Package weight(Lbs)	0.79 kg (1.74 lb(US))
Returnability	No
Country of origin	MX

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

## Contractual warranty

---

Warranty

18 months

---