

Product availability: Stock - Normally stocked in distribution facility



Main	
Product	Single Throw Safety Switch
Current Rating	30 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 1 steel
Factory Installed Neutral	None
Disconnect Type	Non-fusible disconnect
Short Circuit Current Rating	200 kA maximum
Mounting Type	Surface
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	Heavy duty
Voltage Rating	600 V AC/DC
Wire Size	AWG 12AWG 6 aluminium AWG 14AWG 6 copper

Complementary

Complementary	
Width	191.77 mm (7.55 in)
Height	370.84 mm (14.6 in)
Depth	123.70 mm (4.87 in)
Tightening torque	5.08 N.M (45 lbf.in) 0.02 in² (13.3 mm²) AWG 6) 4.52 N.M (40 lbf.in) 0.01 in² (8.367 mm²) AWG 8) 3.95 N.m (35 lbf.in) 0.000.01 in² (2.065.261 mm²) AWG 14AWG 10)

Ordering and shipping details

Category	00008 - H&HU SW,2&3P,N1,30-200A
Discount Schedule	DE1
GTIN	00785901505723
Package weight(Lbs)	3.45 kg (7.6 lb(US))
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☐ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Contractual warranty	

18 months

Warranty

HU361

Approximate Dimensions

