



Product availability: Stock - Normally stocked in distribution facility



Main

| | |
|-----------------------|-------------|
| Range of product | Motor Logic |
| Thermal overload type | Solid state |

Complementary

| | |
|--------------------------------|--------------------|
| NEMA size | 2 |
| Phase | 3 phase |
| Mounting support | Panel |
| [Ue] rated operational voltage | 600 V AC |
| Height | 3.51 in (89.2 mm) |
| Width | 4.28 in (108.7 mm) |
| Depth | 3.51 in (89.2 mm) |

Ordering and shipping details

| | |
|---------------------|--|
| Category | 21662 - 9065 SOLID STATE OVERLOAD RELAYS |
| Discount Schedule | CP1 |
| GTIN | 00785901750000 |
| Package weight(Lbs) | 0.59 kg (1.31 lb(US)) |
| Returnability | Yes |
| Country of origin | MX |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|