

## Product data sheet

### Characteristics

# 8502SDO2V02S

Type S nonreversing magnetic contactor, NEMA Size 2, 3 P, 110/120 VAC 50/60 Hz coil, melting alloy overload, open

Product availability: Stock - Normally stocked in distribution facility




### Main

Product or component type	Contactor
Type	8502S
Control Circuit Type	Separate control circuit
Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Contactor Type	Non-reversing
Current Rating	45 A
Number of Poles	3P
Phase	3 phase
Horsepower Rating	10 HP 200 V AC 15 HP 230 V AC 25 HP 460 V AC 25 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	No control units
Pilot Light	No indicator
Auxiliary Contacts	Without
Control Circuit Fusing	Fuse not supplied
Electrical connection	Screw clamp terminals
Enclosure Type	Not rated (open device)
Product certifications	UL listed CSA
NEMA size	2
Height	5.12 in (130 mm)
Depth	4.92 in (125 mm)
Width	4.92 in (125 mm)

### Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901881612
Package weight(Lbs)	2.59 kg (5.72 lb(US))
Returnability	Yes
Country of origin	MX

### Offer Sustainability

EU RoHS Directive	Not compliant
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

### Contractual warranty

Warranty	18 months
----------	-----------