



Product availability: Stock - Normally stocked in distribution facility



Main

Product or component type	Circuit breaker
Range of product	I-Line
Trip Unit Type	Thermal-magnetic
Rating Code	A

Complementary

Line Rated Current	70 A
Number of Poles	3P
Interrupt Rating	10 KA 250 V DC 25 KA 240 V AC 18 kA 480 V AC
[Ue] rated operational voltage	250 V DC 480 V AC
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
Wire Gauge	AWG 14...AWG 1/0 copper)1 AWG 12...AWG 1/0 aluminium)1
Terminal Type	AL100FA
Magnetic hold current	800 A
Magnetic tripping current	1450 A
Phase connection	ABC
Height	162.56 mm (6.4 in)
Width	114.30 mm (4.5 in)
Depth	104.90 mm (4.13 in)

Environment

Product certifications	UL listed CSA
------------------------	------------------

Ordering and shipping details

Category	00902 - FAL 480V BREAKERS & SWITCH
Discount Schedule	DE2
GTIN	00785901423409
Package weight(Lbs)	2.11 kg (4.65 lb(US))
Returnability	No
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause Birth Defects or other reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------