

Product availability: Non-Stock - Not normally stocked in distribution facility



Main

| | |
|---------------|-----------------|
| Product range | 8501R |
| Product type | Miniature Relay |
| Relay type | Low voltage |

Complementary

| | |
|------------------------------|--|
| Mounting type | Socket |
| Contact composition | 4PDT |
| [Uc] control circuit voltage | 48 V AC |
| Pilot light | No indicator |
| Manual operator | Without test button |
| Horsepower rating | Not rated |
| Breaking capacity | 5 A 120 V AC resistive control circuit UL 508 5 A 240 V AC resistive control circuit UL 508 5 A 30 V DC resistive control circuit UL 508 |
| Maximum switching voltage | 30 V DC 240 V AC |
| Contact material | Hermetically sealed silver tin oxide |
| Operating time | 20 ms - pick-up 20 ms - drop-out |
| Shape of pins | Spade |
| For use with | 8501NR45 |
| Height | 1.16 in (29.4 mm) |
| Width | 0.91 in (23.1 mm) |
| Depth | 1.53 in (38.9 mm) |

Environment

| | |
|---|---|
| Ambient temperature range - operational | -40...55 °C (-40...131 °F) |
| Product certifications | UL listed UL recognized CSA CE |

Ordering and shipping details

| | |
|---------------------|-----------------------|
| Category | 21143 - 8501 R |
| Discount Schedule | CP2 |
| GTIN | 00785901975328 |
| Package weight(Lbs) | 0.05 kg (0.12 lb(US)) |
| Returnability | No |
| Country of origin | CN |

Offer Sustainability

| | |
|----------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds and Di-isodecyl phthalate (DIDP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|