# Product data sheet Characteristics

# QO816L100DS LOAD Center QO MLO 240V 100A 1PH 8SP N1



Product availability: Stock - Normally stocked in distribution facility



#### Main

Product	Load Center
Marketing Trade Name	QO
Cover type	Surface cover with door

#### Complementary

Load Center Type	Main lugs
Line Rated Current	100 A
Number of spaces	8
Short Circuit Current Rating	10 kA
Maximum Number of Single Pole Circuits	16
Maximum Number of Tandem Breakers	8
Number of Phases	1 phase
Voltage Rating	120/240 V AC
Wire Size	AWG 8AWG 1 aluminium/copper
Electrical Connection	Lugs
Grounding Bar	Grounding bar (ordered separately)
Electrical connection	Lugs
Wiring configuration	3-wire
Busbar Material	Tin plated aluminium busbar
Enclosure Material	Welded sheet steel
Cover Finish	Baked enamel grey
Box number	4
Height	12.56 in (319 mm)
Width	8.90 in (226 mm)
Tightening torque	5.65 N.M (50 lbf.in) AWG 8) 5.65 N.m (50 lbf.in) AWG 6AWG 1/0)

#### **Environment**

Enclosure Rating	NEMA 1 indoor
Ambient air temperature for operation	23 °F (-5 °C) 104 °F (40 °C)
Product certifications	UL listed

## Ordering and shipping details

Catagoni	00404 OO 4DUU C 2 9CVT NEMA 4 2D
Category	00101 - QO 1PH LC,2-8CKT,NEMA 1,3R
Discount Schedule	DE3A
GTIN	00785901785743
Package weight(Lbs)	3.74 kg (8.25 lb(US))
Returnability	Yes
Country of origin	MX

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	<sup>™</sup> REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

#### Contractual warranty

o o na a o tali. Na ina ina ina		
Warranty	18 months	