

Product data sheet

Characteristics

8536SDO1V02H30S

Type S nonreversing magnetic starter, NEMA Size 2, 3 P, 110/120 VAC 50/60 Hz coil, Motor Logic overload, open

Product availability: Stock - Normally stocked in distribution facility



Main

Product or component type	Starter
Type	S
Control Circuit Type	Separate control circuit

Complementary

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	45 A
Number of Poles	3P
Number of Phases	3 phase
Horsepower Rating	10 HP 200 V AC 15 HP 230 V AC 25 HP 460 V AC 25 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	No control units
Thermal overload type	Solid state Motor Logic class 10/20
Electrical connection	Screw clamp terminals
NEMA size	2
Height	7.80 in (198 mm)
Depth	4.92 in (125 mm)
Width	4.29 in (109 mm)
Net weight	6.99 lb(US) (3.17 kg)

Environment

Enclosure Type	Not rated (open device)
Product certifications	UL listed NEMA CSA

Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901807094
Package weight(Lbs)	3.17 kg (6.98 lb(US))
Returnability	Yes
Country of origin	MX

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------