

TPRAN2X1

Analog IO module, TeSys island, 2 inputs, 1 output



Product availability: Stock - Normally stocked in distribution facility



Main

Range	TeSys
Product name	TeSys island
Device short name	TPRAN
Product or component type	Analog IO module
Device presentation	IO module providing 2 analog inputs and 1 analog output Enabling advanced control functions in a TeSys island system Operational only when connected to a bus coupler TPRBC
Function of module	Measurement of voltage, current or temperature on 2 configurable analog inputs Driving voltage or current source on 1 configurable analog output
Product compatibility	TPRBC bus coupler
Analogue input number	2
Analogue input type	Current 4...20 mA Current 0...20 mA Voltage 0...10 V Voltage - 10...10 V Temperature probe - 60...180 °C Ni 100 Temperature probe - 60...180 °C Ni 1000 Temperature probe -200...+850 °C Pt 100 Temperature probe - 200...600 °C Pt 1000 Thermocouple - 200...1000 °C thermocouple J Thermocouple - 200...1300 °C thermocouple K Thermocouple 0...1760 °C thermocouple R Thermocouple 0...1760 °C thermocouple S Thermocouple 0...1820 °C thermocouple B Thermocouple - 200...400 °C thermocouple T Thermocouple - 200...1300 °C thermocouple N Thermocouple - 200...800 °C thermocouple E Thermocouple 0...2315 °C thermocouple C
Measurement accuracy	+/- 0.1 % of full scale +/- 0.1 % of full scale +/- 0.1 % of full scale +/- 0.1 % of full scale in positive temperature range +/- 0.4 % of full scale in negative temperature range
Analogue input resolution	15 bits + sign
Input impedance	<= 50 Ohm current >= 1 MOhm voltage >= 1 MOhm thermocouple >= 1 MOhm temperature probe
Analogue output number	1 isolated
Analogue output type	Current 4...20 mA Current 0...20 mA Voltage 0...10 V Voltage - 10...10 V
Analogue output resolution	4...20 mA, full scale 0...20 mA, full scale 0...10 V, full scale - 10...10 V, full scale
Type of cable	Twisted shielded pairs cable <98.43 ft (30 m) input/output
Local signalling	DS (device status) 1 LED green/red

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Complementary

[Us] rated supply voltage	24 V DC supplied by the bus coupler
Current consumption	160 mA
Power dissipation in W	0.5 W maximum
[Uimp] rated impulse withstand voltage	0.5 kV IEC 61010-1
Standards	IEC 61010-2-201 UL 61010-2-201 CSA C22.2 No 61010-2-201
Product certifications	CSA UL EAC (pending)
Mounting mode	Horizontal and vertical 35 mm symmetrical rail)
Connections - terminals	Input/Output circuit removable spring terminal block 8 0.00...0.00 in ² (0.2...2.5 mm ²) AWG 24...AWG 14)rigid Input/Output circuit removable spring terminal block 8 0.00...0.00 in ² (0.2...2.5 mm ²) AWG 24...AWG 14)flexible without cable end Input/output circuit removable spring terminal block 8 0.00...0.00 in ² (0.25...2.5 mm ²) AWG 22...AWG 14)flexible with cable end
Width	0.98 in (25 mm)
Height	4.65 in (118 mm)
Depth	4.49 in (114 mm)
Net weight	0.38 lb(US) (0.172 kg)


Environment

Ambient air temperature for storage	-13...158 °F (-25...70 °C)
Ambient air temperature for operation	14...140 °F (-10...60 °C)
Relative humidity	5...95 %
Operating altitude	0...6561.68 ft (0...2000 m) without derating
IP degree of protection	IP20
Pollution degree	2
Protective treatment	TC
Fire resistance	1760 °F (960 °C) UL 94
Shock resistance	15 gn 11 ms) IEC 60068-2-27
Vibration resistance	1.5 mm peak to peak 3...13 Hz) IEC 60068-2-6 1 gn 13...200 Hz) IEC 60068-2-6
Electromagnetic compatibility	Electrostatic discharge immunity test, level 3 8 kV air, 6 kV contact)EN/IEC 61000-4-2) Radiated RF fields, level 3 10 V/m)EN/IEC 61000-4-3) Fast transients immunity test, level 3 2 kV)EN/IEC 61000-4-4) Surge immunity test, level 3 2 kV)EN/IEC 61000-4-5)

Ordering and shipping details

Category	22353 - TESYS ISLAND AUXILIARY DEVICES
Discount Schedule	I12
GTIN	03606489832704
Package weight(Lbs)	0.23 kg (0.51 lb(US))
Returnability	Yes

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile

Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------
