



Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Product or component type	Motor Circuit Protector
Range of product	PowerPact L
Trip Unit Type	Electronic, standard, Micrologic 1.3 M,
Interrupt Code	L
Options	Auxiliary switch 2 NO + 2 NC

Complementary

Protection technology	Current limiter
Line Rated Current	400 A
Number of Poles	3P
Interrupt Rating	65 KA 480 V AC 100 KA 240 V AC 25 kA 600 V AC
Voltage Rating	600 V AC
Mounting mode	Plug-in
Electrical connection	Plug-in line Plug-in load
Terminal Type	AL600LS52K3
Height	314.96 mm (12.4 in)
Width	139.70 mm (5.5 in)
Depth	395.73 mm (15.58 in)
Accessories	Plug-in base not included
Tightening torque	38.94...442.54 lbf.in (4.4...50 N.m) 0.11...0.37 in ² (70...240 mm ²) AWG 2/0...500 kcmil)

Environment

Product certifications	CCC IEC CSA UL listed CE
------------------------	--------------------------------------

Ordering and shipping details

Category	01116 - L ELEC TRIP UNIT MOUNT BREAKER/SW
Discount Schedule	DE2
Package weight(Lbs)	6.80 kg (15 lb(US))
Returnability	No
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP and DIDP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------