# Product data sheet Characteristics

# HGL26045C POWERPACT H-FRAME, CIRCUIT BREAKER, THERMAL-MAGNETIC, 45A, 2P, 600V, 18kA



Product availability: Non-Stock - Not normally stocked in distribution facility



Main		
Product or component type	Circuit breaker	
Range of product	PowerPact H	
Trip Unit Type	Thermal-magnetic	
Breaking capacity code	G	

### Complementary

Line Rated Current	45 A	
Number of Poles	2P	
Interrupt Rating	20 KA 500 V DC	
	65 KA 240 V AC	
	35 KA 480 V AC	
	18 KA 600 V AC	
	20 kA 250 V DC	
[Ue] rated operational voltage	250 V DC	
	600 V AC	
	500 V DC	
Continuous current rating	100 %	
Mounting mode	Unit mount	
Electrical connection	Lugs load	
	Lugs line	
Wire Gauge	AWG 14AWG 3/0 aluminium/copper	
Magnetic hold current	400 A	
Magnetic tripping current	850 A	
Height	162.56 mm (6.4 in)	
Width	69.60 mm (2.74 in)	
Depth	110.74 mm (4.36 in)	
Tightening torque	44.25 lbf.in (5 N.m) 0.000.15 in² (2.595 mm²) AWG 14AWG 3/0)	

#### Environment

Product certifications	CE UL listed CSA IEC
Ambient air temperature for operation	104 °F (40 °C)

# Ordering and shipping details

Category	01115 - HG,HJ,JG,JJ UNIT MT BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901496014
Package weight(Lbs)	1.36 kg (3 lb(US))
Returnability	Yes
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP and DIDP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	☐ REACh Declaration
EU RoHS Directive	Compliant E EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☐ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

## Contractual warranty

Warranty	18 months