

VLS3P025R1

TeSys VLS - Body switch disconnecter - 3 poles - 25 A - on DIN rail

Product availability: Stock - Normally stocked in distribution facility



Main

Range	TeSys
Product name	TeSys VARIO LS
Device short name	VLS3P
Product or component type	Switch body
Performance level	High performance
Poles description	3P
Contacts type and composition	3 NO
Network type	AC
Network frequency	50/60 Hz
Control type	Rotary handle
Rotary handle mounting style	Direct
Handle colour	Black
Handle front plate colour	Grey
Suitability for isolation	Yes

Complementary

Rotary handle padlocking	1 padlock 0.16 in (4 mm)
Marking	0 - 1
Mounting support	Back DIN rail
Fixing mode	By clips back
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	25 A 131 °F (55 °C)
[Ithe] conventional enclosed thermal current	25 A
[Ie] rated operational current	25 A AC-21A Ue: 400 V 25 A AC-21A Ue: 500 V 25 A AC-21A Ue: 690 V 25 A AC-22A Ue: 400 V 25 A AC-22A Ue: 500 V 25 A AC-22A Ue: 690 V 25 A AC-23A Ue: 400 V 25 A AC-23A Ue: 500 V 25 A AC-23A Ue: 690 V 25 A Ue: 600 V UL 508
Rated operational power in W	22 KW 690 V AC-23A) 11 KW 400 V AC-23A) 15 kW 500 V AC-23A)
Intermittent duty class	Class 120 - 60 %
Making capacity (I Rms)	37.5 A 690 V AC-21A 75 A 690 V AC-22A 250 A 690 V AC-23A
[Icm] rated short-circuit making capacity	1128 A 690 V
[Icw] rated short-time withstand Rms current	800 A 690 V 1 s
Rated conditional short-circuit current	50 kA 400 V 25 A gG
Breaking capacity	37.5 A 690 V AC-21A) 75 A 690 V AC-22A) 200 A 690 V AC-23A)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Device composition	Switch Handle
Mechanical durability	100000 cycles
Electrical durability	100000 cycles AC-21A
Connections - terminals	Power circuit screw clamp terminals 0.02 in ² (10 mm ²) solid Power circuit screw clamp terminals 0.02 in ² (16 mm ²) flexible - without cable end
Tightening torque	Power circuit 15.93...17.70 lbf.in (1.8...2 N.m) screw clamp terminals
Height	2.95 in (75 mm)
Width	1.42 in (36 mm)
Depth	3.07 in (78 mm)
Product weight	0.30 lb(US) (0.135 kg)
Color	Grey

Environment

Standards	IEC 60947-3 CSA C22.2 No 14 UL 508
Product certifications	GL
IP degree of protection	IP20 IEC 60529
Mechanical robustness	Vibrations 2...100 Hz Fc 0.7 g) IEC 60068-2-6 Shocks 11 ms Ea 15 gn) IEC 60068-2-27
Ambient air temperature for operation	-13...131 °F (-25...55 °C)
Fire resistance	1760 °F (960 °C) IEC 60695-2-11

Ordering and shipping details

Category	21734 - TESYS VLS DISCONNECT SWITCHES
Discount Schedule	CP1
GTIN	00785901560425
Package weight(Lbs)	0.18 kg (0.39 lb(US))
Returnability	Yes
Country of origin	IT

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration