HOM2040M200PCVP

Homeline, LC, 200 A, 120/240 V, 1 PH, MB, PoN, 20 SP, N1, combo, VP



Product availability: Stock - Normally stocked in distribution facility



Main	
Product or component type	Load Center value pack
Marketing Trade Name	Homeline
Load center type	Main breaker
Line Rated Current	200 A
Number of spaces	20
Number of circuits	40
Enclosure Rating	NEMA 1 indoor
Cover type	Combination flush/surface cover
Electrical connection	Lugs
Included Options	Circuit breaker 1) 2P 200 A 120/240 V AC main supply ready assembled Circuit breaker 3) 1P 20 A 120/240 V AC Circuit breaker 2) 2P 30 A 120/240 V AC

Complementary

Short-circuit current	22 kA
Number of Tandem Breakers	20
Number of Phases	1 phase
[Ue] rated operational voltage	120/240 V AC
Wire Size	AWG 4250 kcmil aluminium/copper
Wiring configuration	3-wire
Cover finish	Gray baked enamel
Busbar Material	Tin plated aluminium busbar
Enclosure material	Welded sheet steel
Surface finish	Baked enamel grey
Box number	9
Height	29.84 in (758 mm)
Width	14.25 in (362 mm)
Depth	3.74 in (95 mm)

Environment

Ambient air temperature for operation	23 °F (-5 °C) 104 °F (40 °C)
Product certifications	UL E-6294

Ordering and shipping details

00185 - MISC. HOM LOAD CENTERS
DE3C
00785901977063
13.88 kg (30.59 lb(US))
Yes
US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant E EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☐ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations