



Main

| | |
|-----------------------------|--|
| Product or component type | Circuit breaker |
| Range of product | PowerPact P |
| Current sensor rating range | 1200 A |
| Line Rated Current | 1200 A |
| Breaking capacity | 65 KA 240 V AC 35 KA 480 V AC 18 KA 600 V AC |
| AWG gauge | AWG 3/0...500 kcmil aluminium/copper)4 |
| Trip unit technology | Electronic, standard, Micrologic 5.0, LSI |

Complementary

| | |
|--------------------------------|--|
| Product certifications | CSA UL listed IEC |
| [Ue] rated operational voltage | 600 V AC |
| Module type | P-Frame |
| Mounting location | Bolt-on |
| Mounting mode | Unit mount |
| Poles description | 3P |
| Breaking capacity code | G |
| Electrical connection | Lugs load Lugs line |
| Continuous current rating | 100 % |
| Device short name | A |
| Height | 410.46 mm (16.16 in) |
| Depth | 204.47 mm (8.05 in) |
| Width | 210.06 mm (8.27 in) |
| Tightening torque | 442.54 Lbf.in (50 N.m) 0.15...0.37 in ² (95...240 mm ²) AWG 3/0...500 kcmil) 8.85...11.51 lbf.in (1.0...1.3 N.m) |

Ordering and shipping details

| | |
|---------------------|-------------------------------------|
| Category | 01215-PG,H,J,K,L,N UNIT MT BREAKERS |
| Discount Schedule | DE2 |
| GTIN | 00785901571278 |
| Package weight(Lbs) | 32.00 lb(US) (14.515 kg) |
| Returnability | Yes |
| Country of origin | US |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: DIDP and DINP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|