

# Product data sheet

## Characteristics

# SDSA1175

Surge Protect, 36kA, 120/240 VAC, 1 P, 3 W, T4X

Product availability: Stock - Normally stocked in distribution facility



## Main

Product	Surge protection device
Range	Square D

## Complementary

Surge Current	36 kA per phase
Voltage Rating	120/240 V AC
Number of Phases	1 phase
Wiring Configuration	3-wire
MCOV	150 V
Nominal Discharge Current	10 kA
SCCR	25 kA
Local Signalling	Status LED green normal operation
Height	57.15 mm (2.25 in)
Width	57.15 mm (2.25 in)
Depth	68.58 mm (2.7 in)

## Environment

Enclosure Rating	NEMA 4X
Enclosure Material	Black plastic
Standards	UL 1449:ed. 4 type I NEC 285 CSA C22.2 No 8
Ambient Operating	149 °F (65 °C)

## Ordering and shipping details

Category	08462 - SURGE PROTECTION SDSA
Discount Schedule	DE1B
GTIN	00785901210870
Package weight(Lbs)	0.32 kg (0.7 lb(US))
Returnability	Yes
Country of origin	MX

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals which are known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant

Contractual warranty

Warranty	18 months
----------	-----------

---

Approximate Dimensions

---

